



**PREMIER FINISHES INC.**

**Product Safety Data Sheet  
11-201 Hardwood Stain Satin**

Trade Secret. See OSHA 1910.1200(j)

**SECTION 1: Identification**

**Product identifier**

Product name 11-201 Hardwood Stain Satin  
Product number 11-201

**Supplier's details**

Name Premier Finishes Inc.  
Address PO Box 3146  
Oregon City, OR 97045  
USA  
  
Telephone 503-241-2770  
Fax 503-912-1439  
email office@premierfinishes.net

**SECTION 2: Hazard identification**

**Classification of the substance or mixture**

GHS classification in accordance with: (US) OSHA (29 CFR 1910.1200)

GHS label elements, including precautionary statements

**Pictogram**



1. Exclamation mark

**Signal word**

**Warning**

**Hazard statement(s)**

H317 May cause an allergic skin reaction  
H303 May be harmful if swallowed  
H333 May be harmful if inhaled

**Precautionary statement(s)**

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P501 Dispose of contents/container to an approved waste disposal plant.  
P102 Keep out of reach of children.  
P103 Read label before use.

# Product Safety Data Sheet

## 11-201 Hardwood Stain Satin

### SECTION 3: Composition/information on ingredients

#### Mixtures

Any concentration shown as a range is to protect confidentiality or due to batch variation.  
See also OSHA 1910.1200(i)

#### Hazardous components

##### 1. Transparent Yellow Oxide

Concentration 1 - 5 %

H317

May cause an allergic skin reaction

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled

##### 2. Trans Red Oxide

Concentration 0.01 - 1 %

- Flammable liquids (chapter 2.6), Cat. 3

- Sensitization, skin (chapter 3.4), Cat. 1

- Carcinogenicity (chapter 3.6), Cat. 2

- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3

##### 3. Propylene Glycol

Concentration 1 - 5 %

CAS no. 57-55-6

##### 4. Dipropylene glycol monomethyl ether

Concentration 1 - 5 %

CAS no. 34590-94-8

- Flammable liquids (chapter 2.6), Cat. 4

- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3

H227

Combustible liquid

H335

May cause respiratory irritation

H336

May cause drowsiness or dizziness

#### Trade secret statement (OSHA 1910.1200(i))

Any concentration shown as a range is to protect confidentiality or due to batch variation.  
See also OSHA 1910.1200(i)

### SECTION 4: First-aid measures

#### Description of necessary first-aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.  
Move out of dangerous area.

If inhaled

Call a poison center or doctor if you feel unwell. May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain, nausea, dizziness, breathing difficulty, headaches, and loss of coordination. Effects from vapors or spray mists in poorly ventilated areas may include irritation of the mucus membranes.

# Product Safety Data Sheet

## 11-201 Hardwood Stain Satin

In case of skin contact	Wash with plenty of soap and water for at least 15 minutes. Call a poison center or doctor if you feel unwell. May cause skin irritation or sensitivity. Signs/symptoms may include localized redness, cracks, swelling, itching, and dermatitis.
In case of eye contact	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.
If swallowed	Call a poison center or doctor if you feel unwell. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Delayed symptoms and effects: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

### SECTION 5: Fire-fighting measures

#### Suitable extinguishing media

Foam, alcohol foam, CO<sub>2</sub>, dry chemical, water fog. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Specific hazards arising from the chemical

Closed containers may rupture if exposed to fire or extreme heat due to build-up of steam pressure.

Trans Red Oxide: Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

#### Special protective actions for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Water spray may be used to cool closed containers to prevent pressure build-up and possible rupture of containers.

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

#### Environmental precautions

Keep out of drains, sewers, ditches, and waterways.

#### Methods and materials for containment and cleaning up

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

### SECTION 7: Handling and storage

#### Precautions for safe handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

# Product Safety Data Sheet

## 11-201 Hardwood Stain Satin

### Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Keep out of the reach of children. Do not freeze. Product will not recover.

## SECTION 8: Exposure controls/personal protection

### Control parameters

#### CAS: 34590-94-8

Dipropylene glycol methyl ether

ACGIH (USA): 100 ppm, (ST) 150 ppm TLV® inhalation; NIOSH: 100 ppm, (ST) 150 ppm REL inhalation; OSHA: 100 ppm PEL inhalation;

### Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Individual protection measures, such as personal protective equipment (PPE)

#### Pictograms



#### Eye/face protection

Safety glasses with side-shields.

#### Skin protection

Protective gloves and impervious clothing.

#### Body protection

Wear suitable protective clothing.

#### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.)	Liquid
Odor	No data available.
Odor threshold	Not determined.
pH	8.5-9.5
Melting point/freezing point	32°F / 0°C
Initial boiling point and boiling range	212°F / 100°C
Flash point	None (closed cup)
Evaporation rate	Slower than ether
Flammability (solid, gas)	Not applicable.

# Product Safety Data Sheet

## 11-201 Hardwood Stain Satin

Vapor density	Heavier than air
Relative density	8.5 wpg
Solubility(ies)	No data available.
Partition coefficient: n-octanol/water	No data available.
Auto-ignition temperature	None
Decomposition temperature	No data available.
Viscosity	KREBS 59-62KU
Explosive properties	None
Oxidizing properties	No data available.

### SECTION 10: Stability and reactivity

#### Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### Chemical stability

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.  
Hazardous polymerization does not occur.

#### Conditions to avoid

No data available.

#### Incompatible materials

No data available.

Trans Red Oxide: Reactive or incompatible with the following materials: oxidizing materials.

#### Hazardous decomposition products

No data available.

Transparent Yellow Oxide: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Trans Red Oxide: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### Information on toxicological effects

##### Acute toxicity

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

##### Skin corrosion/irritation

May cause skin irritation. Signs/symptoms may include localized redness, cracks, swelling, dermatitis and itching.

##### Serious eye damage/irritation

May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, burning, blurred or hazy vision.

##### Respiratory or skin sensitization

No data available.

# Product Safety Data Sheet

## 11-201 Hardwood Stain Satin

Trans Red Oxide: Can cause central nervous system depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact...May cause allergic skin reaction.

### **Germ cell mutagenicity**

No data available.

### **Carcinogenicity**

No data available.

Trans Red Oxide: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

### **Reproductive toxicity**

No data available.

### **Summary of evaluation of the CMR properties**

No data available.

### **STOT-single exposure**

No data available.

### **STOT-repeated exposure**

No data available.

### **Aspiration hazard**

No data available.

### **Additional information**

No data available.

## **SECTION 12: Ecological information**

### **Toxicity**

No data available.

### **Persistence and degradability**

No data available.

Dipropylene glycol monomethyl ether: Biodegradability aerobic - Exposure time 28 d  
Result: 76 % - Readily biodegradable  
(OECD Test Guideline 301F)

### **Bioaccumulative potential**

No data available.

Dipropylene glycol monomethyl ether:

<http://webnet.oecd.org/ccrweb/ChemicalDetails.aspx?ChemicalID=0F505FF5-E297-4D11-B841-AE6B73A2C59C>

Does not bioaccumulate

### **Mobility in soil**

No data available.

### **Results of PBT and vPvB assessment**

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

# Product Safety Data Sheet

## 11-201 Hardwood Stain Satin

### Other adverse effects

No data available.

## SECTION 13: Disposal considerations

### Disposal of the product

Dispose of contents in accordance with local regulations.

### Disposal of contaminated packaging

Dispose of containers in accordance with local regulations.

### Waste treatment

Dispose of contents/containers in accordance with local regulations.

### Sewage disposal

Dispose of contents/containers in accordance with local regulations.

### Other disposal recommendations

Dispose of contents/containers in accordance with local regulations.

## SECTION 14: Transport information

### DOT (US)

Not dangerous goods

### IMDG

Not dangerous goods

### IATA

Not dangerous goods

## SECTION 15: Regulatory information

### Safety, health and environmental regulations specific for the product in question

#### Massachusetts Right To Know Components

Chemical name: Propanol, (2-methoxymethylethoxy)-

CAS number: 34590-94-8

#### New Jersey Right To Know Components

Common name: DIPROPYLENE GLYCOL METHYL ETHER

CAS number: 34590-94-8

#### Pennsylvania Right To Know Components

Chemical name: Propanol, (2-methoxymethylethoxy)-

CAS number: 34590-94-8


### HMIS Rating

11-201 Hardwood Stain Satin	
HEALTH	1
FLAMMABILITY	
PHYSICAL HAZARD	
PERSONAL PROTECTION	B

# Product Safety Data Sheet

## 11-201 Hardwood Stain Satin

### NFPA Rating



### SECTION 16: Other information

Do not freeze. Product will not recover.

#### Further information/disclaimer

While the description, data, and information contained herein are presented in good faith and believed to be accurate, it is provided for guidance only. Because many factors may affect application/use, it is recommended that you make tests to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding the product described, data, or information set forth, or that the product, data, or information may be used without infringing the intellectual property rights of others. In no case shall the description, information, or data provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree the description, data, and information furnished herein are provided gratis and we assume no obligation or liability for the description, data, and information given or results obtained, all such being given and accepted at your risk. The content of this SDS (a.k.a. MSDS) is copyrighted [(c) PFI]. This SDS may be shared, without changes, and no changes to the PFI content are authorized. Updates to all PFI SDS documents must be obtained directly from PFI. See Section 1 for PFI contact and website information.