



**Certificate
Of
Analysis**

**Product #
10-876**

(Promar 700 offset)

**Super-Flat
Interior Latex Primer Finish**

Super-Flat Interior Latex Primer-Finish is an economical interior wall paint for use on walls and ceilings of primed plaster, wallboard, wood, masonry and primed metal surfaces.

PHYSICAL CHARACTERISTICS

Weight per gallon:	11.15
% Solids by Weight:	47.07
%Solids by Volume:	29.02
Viscosity Krebs:	105 KU
Flash Point (closed cup):	none
Spread Rate:	350-400 sq ft/gal
Material VOC:	0.15 lb /
Coatings VOC (-water):	0.42 lb /
Color:	White
Dry-time @ 77F 50% RH:	1 hr-Touch
Dry Time:	4 hrs- Recoat

Application

Apply at temperatures above 50F. No reduction needed. Use a nylon/polyester brush, or a 3/8 to 3/4 inch nap synthetic cover. For spray applications, use airless spray apparatus at approximately 2000 p.s.i. with a .017-.021 inch tip.

Make sure product is completely agitated prior to use. Priming and application of two coats at the recommended film thickness can improve hide of previous coatings. This is also useful over new drywall.

Use the same method of application and batch for touch up color consistency.

Clean up with warm soapy water.