

## LED STRIP - SPARKLE SERIES



### SPECIFICATIONS:

<b>Power:</b>	4.4 W/ft
<b>Lumens:</b>	330-360 lm/ft
<b>CRI:</b>	>80
<b>LED Qty:</b>	18/ft (60/m)
<b>Field Cuttable:</b>	Every 1.97" (5 cm)
<b>Input Voltage:</b>	12VDC Constant Voltage
<b>Light Source:</b>	SMD5050
<b>CCT:</b>	3000K, 6000K, 10000K
<b>CRI:</b>	>80
<b>Max Run:</b>	24 ft
<b>Beam Angle:</b>	120°
<b>Dimensions:</b>	0.2" (5 mm) - width
<b>Life Time:</b>	30,000 hrs
<b>Certifications:</b>	CE
<b>Operating Temp:</b>	-4° ~ 104° (F)
<b>Warranty:</b>	2 Years
<b>Usage:</b>	Indoor/dry location
<b>Mounting:</b>	Double-sided tape adhesive
<b>Dimmable:</b>	Yes
<b>End Wire:</b>	2 wire lead

### NOTES

- Must be connected to a 12VDC power supply.
- Dimmable
- Do not install in wet/humid location. If installed in wet/humid location, waterproof enclosure must be used.
- After each maximum run, a separate power source (12 VDC) is needed.
- LED Bar is sold in 0.5 m length.
- When ordering, inquire the desired lengths for accurate number of connections.

Incolight - SPARKLE LED Bar Series is the best LED lighting for Show cases. Available in 10000K, this LED bar is perfect for jewelry (diamond) applications requiring extremely bright cool white light. SPARKLE LED Bars are field cuttable and are suitable for any size or type of show or wall cases.


### APPLICATIONS

- Show cases
- Wall cases
- Cove lighting
- Under the cabinet
- Window display

### COMPATIBILITY

Aluminum Profile - AP0915-45D

- Perfect for show cases - slim design. Give maximum exposure of products
- Unique Design - multiple angle possibilities
- Mounting - Doubled tape - strong adhesive - will not come off by itself



### Ordering Guide:

LS-SPARKLE-60-12V-\_\_\_\_\_

↑

CCT

3K - 3000K

6K - 6000K

10K - 10000K

Example: LS-SPARKLE-60-12V-10K

LED LIGHTING - LED STRIP - SPARKLE