

# **5**Seconds<sup>TM</sup>

**5 SECONDS<sup>TM</sup> 1SYS300 POLYPROPYLENE  
SEMI AUTO BOX STRAPPING MACHINE**



## DESCRIPTION

The 1SYS300 Polypropylene Semi Auto Box Strapping Machine is a general purpose strapping machine that can strap package quickly and efficiently. Strapping cycle will automatically start when operator inserts strap. The machine will automatically shut down after the preset time to save electricity. This machine is recommended for strapping cartons in light industry settings.

## FEATURE

- Front control panel makes adjustments fast and easy
- Speeds up productivity by dispensing, tightening, and sealing up to 24 straps/min
- Heat weld - No seals required
- Enclosed frame to keep dust and dirt out
- Minimum Box Requirements: 3 1/2" Long And 2" High
- Maximum Box Requirements: No Upper Limit
- Fast warm up (approximately 5 minutes)
- Control panel to adjust reset and manual feed buttons
- Tension Range Adjustment: 2-100 lbs/in

# Basic Information

	Specification
SKU #	999012
Power Source	110-120/200-240V 50/60Hz 1 PH 0.25kW 2.5A
Packing Speed	≤3 Second/path
Tension Range	11lbs - 110.2lbs
Hot-adhering Position	Bottom
Working Table Height	28.7"
Min. Packaging Size	2.3"*2.3"
Applicable PP Strap	Width: 5mm-15mm, Thickness:0.5mm-0.85mm
Applicable Pp Strap Spool	Inner Dia.: 7.8"~8.2", Outer Dia.: 15.7"~19.6", Width: 6.2"~7.4"
Packing Type	Manual Semi-automatic Packing
Electrical Configuration	P.C. Board Control Electrical: Switching Power Supply Motor: Dc Motor 24v
Machine Size	33.4" x 21.4" x 28.7" (LxWxH)
Shipping Size	34.2" x 22" x 34.2" (LxWxH)
Weight	N.W: 176.3lbs G.W: 198.4lbs
Environment Moisture	35%-85%RH
Transportation/storage Temperature	-25°C-55°C
Bottom Adhesion	Surface≥90%, Width≥20%, Deviation Of Position≤2mm

# DIMENSIONS

