

Digital Mini MultiMeters

 **Compact Autoranging or Manual ranging multimeters**
with Temperature function

Features:

- Large easy to read digital display
- Measure AC and DC Voltage to 600V
- DC Current function to 10A
- Thermocouple Temperature measurements to 1400°F (750°C)
- Resistance tests with Continuity and Diode functions
- Manual ranging model (MN35) with 9V and 1.5V Battery test
- Autoranging model (MN36) with AC Current, Capacitance and Frequency measurements
- Convenient mini size with protective rubber holster and tilt stand
- Data Hold locks reading in the display
- Includes protective rubber holster, battery, Test leads and Type K thermocouple probe



| Specifications | Model MN35 | | Model MN36 | |
|----------------|------------------------------|-----------------|--|-----------------|
| | Range | Max. Resolution | Range | Max. Resolution |
| DC Voltage | 200mV, 2V, 20V, 200V, 600V | 0.1mV | 400mV, 4V, 40V, 400V, 600V | 0.1mV |
| AC Voltage | 200V, 600V | 0.1V | 4V, 40V, 400V, 600V | 0.1V |
| DC Current | 200mA, 10A | 0.1mA | 400µA, 4000µA, 40mA, 200mA, 10A | 0.1µA |
| AC Current | — | — | 400µA, 4000µA, 40mA, 200mA, 10A | 0.1µA |
| Resistance | 200Ω, 2kΩ, 20kΩ, 200kΩ, 20MΩ | 0.1µΩ | 400Ω, 4kΩ, 40kΩ, 400kΩ, 4MΩ, 40MΩ | 0.1Ω |
| Capacitance | — | — | 4nF, 40nF, 400nF, 4µF, 100µF | 0.001nF |
| Frequency | — | — | 10Hz, 100Hz, 1kHz, 10kHz, 100kHz, 1MHz, 5MHz | 0.01Hz |
| Temperature | -4 to 1400°F (-20 to 750°C) | 1° | -4 to 1400°F (-20 to 750°C) | 1 |
| Battery Test | 9V and 1.5V Batteries | — | — | — |
| Power | one 9V battery | — | 2 x AAA batteries | — |
| Dimensions | 5.43x2.83x1.5" (138x72x38mm) | — | 5.43x2.83x1.5" (138x72x38mm) | — |
| Weight | 5.4oz (153g) | — | 5.4oz (153g) | — |

Ordering Information:

MN35Manual Ranging Mini MultiMeter
MN36Autoranging Mini MultiMeter



*MN36 only