

## Sealock SU2009

---



Made of 51mm wide steel that is 6mm thick, the Sealock Model SU2009 requires two cuts and two tools to remove. This need for both a power cutting tool such as an angle grinder and a cable cutter prevents break-ins by thieves who generally do not carry such sophisticated tools with them.

### Applications

Intermodal Containers / ISO Containers

### Custom Options

- Heat or cold stamped with seven alphanumeric characters
- Characters are 5mm in height

## Sealock SU2009

### Features

- Numbered steel braided aircraft cable with bullet tip is an integral part of the locking system. (U.S. Patent No. 6,331,022)
- Two-tone baked on enamel finish, engraved markings on the J-Bar and Bracket, and plastics utilized at strategic points make it easy to spot tampering. (U.S. Patent No. 6,536,815)
- Braided cable frays when cut.
- Same numerical sequence appears on all three components for added security.
- Extended return on the J-Bar.
- Designed to fit most Swing Door Conveyances.
- J-Bar 500 x 40mm / Cable 270mm

### Material

J-Bar 100% Steel  
construction Steel braided  
aircraft cable

### Carton (10 Units)

Weight: 25kg

### Strength Characteristics

Load Force Minimum (Nm)  
88.9 Load Force Maximum  
(Nm) 133.4 Average (Nm)  
111.1

*Portable device.  
Mounts in seconds  
without tools.*



*Dual function.  
Provides both a sealing  
and locking function  
simultaneously.*



*Removal requires  
two separate cuts.  
(J-Bar and Cable)*



*Exceeds all ISO/PAS  
17712 & ASTM "F"  
1157 Standards.  
C-TPAT compliant.*

