

Technical specifications

<p>Compliance with standards</p>	<p>EN 50131 (Grade 2) PD 6662:2017</p> <p>Compatibility</p> <p>Hubs all Ajax hubs</p> <p>Range extenders all Ajax radio signal range extenders</p>
<p>Communication with control panel and range extenders</p>	<p>Jeweller communication technology</p> <p>Frequency bands 866.0 - 866.5 MHz 868.0 - 868.6 MHz 868.7 - 869.2 MHz 905.0 - 926.5 MHz 915.85 - 926.5 MHz 921.0 - 922.0 MHz Depends on the region of sales</p> <p>Maximum effective radiated power (ERP) ≤ 20 mW</p> <p>Communication range up to 1,200 m In an open space</p> <p>Polling interval 12-300 sec Adjusted by PRO or user with admin rights in the Ajax app</p> <p>Protection against forgery Device authentication</p> <p>Detection</p> <p>Sensing element 1 x reed switch</p> <p>Opening sensors resource 2,000,000 openings</p> <p>Third-party detector connection wired detector with the normally closed (NC) contact type</p>

<p>Power supply</p> <p>1 x CR123A, 3 V Pre-installed</p> <p>up to 7 years of battery life</p>	<p>Installation</p> <p>Operating temperature range from -1 O°C to +40°C</p> <p>Operating humidity up to 75%</p> <p>Ingress protection IP50</p>
<p>Enclosure</p> <p>Colours white, black</p> <p>Dimensions 0 20 x 90 mm</p> <p>Weight 29 g</p> <p>Tampering alarm</p>	<p>Complete set</p> <p>DoorProtect Jeweller 2 magnets (small and large) 1 x CR123A (pre-installed) SmartBracket Installation kit Externa! contact far NC detector Quick Start Guide</p>