


# Technical specifications

<p>Compliance with standards</p>	<p><b>EN 50131 (Grade 2)</b> <b>PD 6662:2017</b></p>	<p>Connection to CMS</p>	<p><b>SurGard (Contact ID)</b> <b>SIA (DC-09)</b> <b>ADEMCO 685</b> <b>Other proprietary protocols</b></p>
<p>Connected devices</p>	<p><b>up to 100 wireless devices</b> <b>Including up to 5 range extenders and up to 10 sirens.</b></p>	<p>Features</p>	<p><b>50 users</b> <b>25 cameras or DVRs</b> <b>32 automation scenarios</b> <b>9 security groups</b> <b>photo verification support</b></p>

<p>Communication channels with Ajax devices</p> <p> <b>Jeweller communication technology</b></p> <p><b>Frequency bands</b>  <b>866.0-866.5 MHz</b>  <b>868.0-868.6 MHz</b>  <b>868.7-869.2 MHz</b>  <b>905.0-926.5 MHz</b>  <b>915.85-926.5 MHz</b>  <b>921.0-922.0 MHz</b>  Depends on the sales region.</p> <p><b>Maximum effective radiated power (ERP)</b>  :::25 mW</p> <p><b>Communication range</b>  up to 2,000 m  in an open space.</p>	<p>External communication channels</p> <p><b>Ethernet</b>  8P8C slot  Up to 100 Mb/s.</p> <p><b>Cellular network</b>  1 slot for micro-SIM</p> <p>2G (GSM900/DCS1800 (83/88))</p>
<p>Power supply</p> <p><b>Main power supply</b>  100-240 V<sub>r.J.</sub>, 50/60 Hz</p> <p><b>Backup power supply</b>  Li-Ion battery with 2 A·h capacity  Up to 16 hours of autonomous operation.</p>	<p>Installation</p> <p><b>Operating temperature range</b>  from -10°C to +40°C</p> <p><b>Operating humidity</b>  up to 75%</p> <p><b>Protection class</b>  <b>IP20</b></p>
<p>Enclosure</p> <p><b>Colour</b>  white  black</p> <p><b>Dimensions</b>  163 x 163 x 36 mm</p> <p><b>Weight</b>  362 g</p> <p><b>Tampering alarm</b></p>	<p>Complete set</p> <p><b>Hub 2 (2G) Jeweller</b>  <b>Power cable</b>  <b>Ethernet cable</b>  <b>SIM card</b>  Depends on the region of sale.  <b>Installation kit</b>  <b>Quick Start Guide</b></p>