## **Technical specifications**

Compliance with standards	EN 50131 (Grade 2) PD 6662:2017	Connection to CMS	SurGard (Contact ID) SIA (DC-09) ADEMCO 685 Other proprietary protocols
Connected devices	up to 200 wireless devices Including up to 5 range extenders and up to 1 0 s1 rens	Features	200 users 1 00 cameras or DVRs 64 automation scenarios 25 security groups
Communication channels with Ajax devices	<text></text>	Externa! communication channels	Ethernet 8P8C slot Up to 100 Mb/s Wi-Fi 802.11 b/g/n Cellular network 2 slots for micro-SIMs

Communication channels with Ajax devices Frequency bands 866.0-866.5 MHz 868.0-868.6 MHz 868.7-869.2 MHz 905.0-926.5 MHz 915.85-926.5 MHz 921.0-922.0 MHz Depends on the sales reg1on.

Maximum effective radiated power (ERP) :::25 mW

Jeweller communication range up to 2,000 m In an open space

Wings communication range up to 1,700 m In an open space Externa! communication channels 2G {GSM900/DCS1800 (83/88)) 3G (WCDMA 850/900/2100 {81/85/88)) 4G/LTE (FDD 81/83/85/ 87/88/820)

Power supply

Main power supply 100-240 Vrv, 50/60 Hz Installation

Operating temperature range

from  $-10^{\circ}$ C to  $+40^{\circ}$ C

	Beeleun neuver eurobe		from $-10^{\circ}$ C to $+40^{\circ}$ C
	Backup power supply Li-lon battery with 2 A-h		Operating humidity
	capacity		up to 75%
			Protection class
			IP20
Enclosure	Colour	Complete set	Hub 2 Plus Jeweller
	white, black		Power cable
			Ethernet cable
	Dimensions		SIM card
	163 x 163 x 36 mm		Depends on the region of
			sale
	Weight		1nstallation kit
	351 g		Quick Start Guide
	Tampering alarm		