# **Technical specifications**

Compliance with	EN 50131 (Grade 2)	CMS connectivity	Hubs
standards	PD 6662:2017		Hub 2
			Hub 2 Plus
			Hub Hybrid (2G)
			Hub Hybrid (4G)
			Range extenders
			ReX2
Communication	🦕 Jeweller	Motion detection	Sensitive element
channels with Ajax devices	communication technology		PIR sensor
	₩ings		<b>Detection distance</b>
	communication technology		up to 12 m
			When installed at a heigh
	Frequency bands		of 2.4 m.
	866.0 - 866.5 MHz		
	868.0 - 868.6 MHz		<b>Detection angles</b>
	868.7 - 869.2 MHz		horizontal - 88.5°
	905.0 - 926.5 MHz		vertical - 80°
	915.85 - 926.5 MHz		
	921.0 - 922.0 MHz		Motion detection speed
	Depends on the region of		from 0.3 to 2.0 m/s

sales.

Maximum effective radiated power (ERP) :5 20 mW

### **Communication range**

up to 1,700 m 1n an open space.

### Polling interval

## 12-300 s Adjusted by PRO or user with admin rights in the Ajax app.

## **Protection against forgery**

Device authentication

The direction of the detector lens should be perpendicular to an alleged intrusion path into the facility.

## Temperature compensation

## Sensitivity

3 levels Adjusted by PRO or user with admin rights in the Ajax app.

## Pet immunity

weight: up to 20 kg height: up to 50 cm

Photo verif1cation	Photo resolution in pixels	Installation	Recommended installatio	
	640 x 480		height	
	320 x 240 (default)		2.4 m	
	160 x 120		Operating temperature range	
	Adjusted by PRO or user			
	with admin rights in the			
	Ajax app		from -1 O°C to +40°C	
	Photos in a series		<b>Operating humidity</b>	
	from 1 to 5 pies		up to 75%	
	Adjusted by PRO or user			
	with admin rights in the		Protection class	
	Ajax app		IP50	
	IR backlight			
Power supply	Battery	Enclosure	Colour	
	2 x CR123A		white, black	
	Pre-installed.			
			Dimensions	
	Battery life		110 x 65 x 50 mm	
	up to 4 years			
			Weight	
			86 g	

Complete set	MotionCam (PhOD)	
	Jeweller	
	2 x CR123A battery	
	Pre-installed	
	SmartBracket mounting	
	panel	
	Installation kit	
	Quick Start Guide	