

AXIS M2036-LE Bullet Camera

Affordable camera with deep learning

Ideal for tough environments and rough weather, AXIS M2036-LE delivers Quad HD 1440p/4 MP. With a deep learning processing unit, it enables unique opportunities for analytics based on deep learning on the edge. AXIS Object Analytics offers detection and classification of humans, vehicles, and types of vehicles. And Axis Edge Vault protects your Axis device ID and simplifies authorization of Axis devices on your network. This IK08-rated camera offers flexible and cost-efficient installation including support for PoE. Edge-to-edge technology allows for smart pairing with Axis Speakers. Plus, a spacious, sealed back box ensures secure cable management.

- > **Quad HD 1440p/4 MP**
- > **Compact, lightweight design**
- > **Analytics with deep learning**
- > **Zipstream supporting H.264/H.265**
- > **Outdoor-ready with IR illumination**



AXIS M2036-LE Bullet Camera

Models	AXIS M2036-LE AXIS M2036-LE Black	operating temperature, IP address removed, network lost, new IP address, system ready Video: average bitrate degradation, tampering, day-night mode Application: motion alarm, VMD 4, VMD3 Scheduled and recurring: scheduled event Edge storage: recording ongoing, storage disruption, storage health issues detected MQTT subscribe
Camera		
Image sensor	1/2.7" progressive scan RGB CMOS	
Lens	Fixed iris, fixed focus, IR corrected 2.4 mm, F2.1 Minimum focus distance: 0.5 m 4 MP (16:9) Horizontal field of view: 130° Vertical field of view: 71° 4 MP (4:3) Horizontal field of view: 109° Vertical field of view: 81°	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	With Lightfinder Color: 0.18 lux at 50 IRE, F2.1 B/W: 0.04 lux at 50 IRE, F2.1 0 lux with IR illumination on	
Shutter speed	1/38500 s to 1/5 s	
System on chip (SoC)		
Model	CV25	
Memory	1024 MB RAM, 512 MB Flash	
Compute capabilities	Deep learning processing unit (DLPU)	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	
Resolution	2304x1728 to 320x240 (4:3) 2668x1512 to 640x360 (16:9)	
Frame rate	Up to 25/30 fps with power line frequency 50/60 Hz in H.264 and H.265 ^a	
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265	
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate streaming	
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure control, motion-adaptive exposure, WDR: up to 115 dB depending on scene, text and image overlay, privacy masks, mirroring of images Rotation: 0°, 90°, 180°, 270°, including Corridor Format	
Pan/Tilt/Zoom	Digital PTZ	
Audio		
Audio output	Smart pairing with Axis speakers via edge-to-edge technology	
Network		
Security	Password protection, IP address filtering, HTTPS ^b encryption, IEEE 802.1x (EAP-TLS) ^b network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, signed video, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified)	
Network protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^b , HTTP/2, TLS ^b , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, NTP, NTS, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, DHCPv4/v6, SSH, LLDP, MQTT v3.1.1	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	
Event conditions	I/O: manual trigger Device status: above operating temperature, above or below operating temperature, below operating temperature, within	
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text, day/night mode MQTT publish	
Built-in installation aids	Pixel counter Level grid	
Analytics		
AXIS Object Analytics	Object classes: humans, vehicles (types: cars, buses, trucks, bikes) Trigger conditions: line crossing, object in area, time in area ^{BETA} Up to 10 scenarios Metadata visualized with trajectories and color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event	
Metadata	Object data: Classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates Confidence, position Event data: Producer reference, scenarios, trigger conditions	
Applications	Included AXIS Object Analytics, AXIS Video Motion Detection, active tampering alarm Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	
General		
Casing	IP66-/IP67-, NEMA 4X- and IK08-rated Aluminum and plastic casing AXIS M2036-LE: White NCS S 1002-B AXIS M2036-LE Black: Black NCS S 9000-N	
Sustainability	PVC free, BFR/CFR free	
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 5 W, max 12.95 W	
Connectors	RJ45 10BASE-T/100BASE-TX PoE	
IR illumination	Optimized IR with power-efficient, long-life 855 nm IR LEDs Range of reach 20 m (65.6 ft) or more depending on the scene	
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com	
Operating conditions	-30 °C to 50 °C (-22 °F to 122 °F) Start-up temperature: -30 °C (-22 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Humidity 10–100% RH	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)	
Approvals	EMC CISPR 24, CISPR 35, EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 60950-22, CAN/CSA-C22.2 No. 60950-22, IEC 62471, IS 13252 Environment IEC 60068-2-X, IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK08 Network	

	NIST SP500-267
Dimensions	Length: 170 mm (6.7 in) ø 101 mm (4.0 in)
Weight	491 g (1.1 lb)
Included accessories	Installation guide, Windows® decoder 1-user license, Torx® L-key, connector guard
Optional accessories	AXIS T94B03L Recessed Mount AXIS T94B02D Pendant Kit AXIS T94B01P Conduit Back Box AXIS T94B02M J-Box/Gang Box Plate AXIS T94 mounts for various installations AXIS Surveillance Cards For more accessories, see axis.com

Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners. For more information, see axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
Warranty	5-year warranty, see axis.com/warranty

- a. *Reduced frame rate in Motion JPEG*
- b. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*

Environmental responsibility:

axis.com/environmental-responsibility