

## Double-Door Electromagnetic Locks

**E-941DA-600Q** 600-lb Holding Force per door, UL Listed

**E-941DA-600PQ** 600-lb Holding Force per door, with Bond Sensors, LEDs, UL Listed

**E-941DA-1K2Q** 1,200-lb Holding Force per door, UL Listed

**E-941DA-1K2P** 1,200-lb Holding Force per door, with Bond Sensors, LEDs, UL Listed

### Features:

- ▶ Anodized aluminum housing (US 28).
- ▶ 12 or 24VDC (selectable).
- ▶ No residual magnetism.
- ▶ MOV surge protection.
- ▶ Adjustable mounting bracket.
- ▶ Complete mounting hardware for typical installations.
- ▶ “L” bracket and “Z” brackets available for easy mounting.
- ▶ Detachable faceplate.

### E-941DA-600PQ and E-941DA-1K2P feature:

- ▶ Built-in dual-colored status LEDs and bond sensors to show locking status of each door.

Green	Door is closed and locked
Red	Door not closed and/or locked
Off	Door in use / No power

- ▶ Bond sensor relay: 3A@12VDC.

### Specifications:

	DA-600Q	DA-600PQ	DA-1K2Q	DA-1K2P
Holding force (per door)	600-lb (272kg)		1,200-lb (545kg)	
Operating voltage	12 or 24 VDC ±10%			
Current draw	12VDC	500mA@12VDC		
	24VDC	250mA@24VDC		
Bond sensor relay	3A@12VDC			
Operating temperature	14°~131° F (-10°~55° C)			
Weight	9-lb (4kg)		21-lb (10kg)	
Bond sensor relay		•		•
Status LEDs		•		•



E-941DA-600Q  
(shown)




Magnet Dimensions:  
19<sup>11</sup>/<sub>16</sub>" x 1<sup>5</sup>/<sub>8</sub>" x 1"  
(500 x 42 x 25 mm)



E-941DA-1K2P  
(shown)

Magnet Dimensions:  
21" x 2<sup>5</sup>/<sub>8</sub>" x 1<sup>5</sup>/<sub>8</sub>"  
(536 x 67 x 42 mm)

Complete line of “Z”, “L” and specialty mounting brackets available:



E-941S-1K2/ZQ  
(shown)