

Energy Management Solutions  
Diesel Storage & Dispensing  
UK & Ireland

# FuelMaster<sup>®</sup> TITAN Diesel Storage & Dispensing Solutions

Product Guide

Available from 1,200 - 9,000 Litres



[kingspan.com](http://kingspan.com)



C21.8391.V25

# TITAN FuelMaster®

## Intelligent Diesel Storage & Dispensing Solutions

10 year Tank Guarantee**	HVO Ready

The FuelMaster range is available from 1,200-9,000 litres with a number of specification options and intelligent tank monitoring and management systems to suit any application.



**Power and Safeguard your Business**

- Industry Leading Approvals - CE marked according to EN13341
- Quality Assured - Made in EN ISO 9001:2000 facility
- Environmental Protection - Bunded construction. Meets Environmental Agencies regulations - NIEA, EA and SEPA

# TITAN FuelMaster®

## New & Improved Features

Faster Pumps	Digital Flowmeter	Motion Sensor light

The complete FuelMaster range comes with various specifications to suit all types of user.

### FuelMaster® Standard

Our Standard specification comes with a 72 lpm\* pump, 6m hose, 10 micron filter and mechanical level gauge. With no flow meter, these tanks are suitable for customers with low fuel usage who do not need to record dispensed fuel.

### FuelMaster® Advanced

Advanced is our most popular solution with a much higher specification including; 72 lpm\* pump, digital flow meter, motion sensor light and electronic level gauge. With the ability to record fuel usage these tanks are ideal for most customers requirements.

### FuelMaster® PRO

Our highest specification tanks come with the Watchman Access cloud based fleet management system. This Plug & Play technology offers numerous features and benefits allowing customers to manage and control how fuel is being used and view tank levels remotely resulting in cost savings, security and peace of mind.

Our Advanced and PRO specifications can be upgraded to have 100 lpm\* and 8m hose reel. Please see spec table (page 4) for more information.

### Tank Dimensions

Capacity (Litres/Gallons)	Length (mm)	Width (mm)	Height (mm)
1,200 / 260	1,150	1,200	1,430
1,225 / 270	2,050	900	1,970
1,300 / 285	1,920	1,230	1,785
2,500 / 550	2,460	1,460	1,860
3,500 / 755	2,850	2,200	1,960
5,000 / 1,100	2,850	2,250	2,350
9,000 / 1,980	3,280	2,450	2,950



FuelMaster Advanced 5000L:

1. Bunded Outer Tank
2. Lockable Doors
3. 72 lpm\* Pump 230v
4. Digital Flowmeter
5. 6m hose
6. Auto Shut Off Nozzle
7. 10 Micron Particle & Water Filter
8. 2" BSP Coupling for Filling
9. Drip tray in Cabinet
10. Spillstop Mechanical Overfill Protection
11. Light
12. Motion Sensor & Junction Box
13. Watchman UniRX Electronic Level Gauge
14. Watchman Sonic 4-20mA Electronic Level Gauge
15. Watchman Access Fleet Management\*\*\*

\* Maximum across pump flow rate as defined by pump manufacturer. Actual flowrate will be less.  
 \*\* 10 year warranty applies to tanks only.  
 \*\*\* Available only in PRO specifications.

† Engineer will check installation and perform various system checks (UK mainland only).

## Watchman Access: Fuel Management System

Included with PRO Specifications

- Cloud Based Technology
- Engineer Site Visit†
- Plug & Play Design
- Starter pack of 40 Cards & Fobs
- Roaming SIM Card
- Access to Web Page to View Data
- Full Technical Support



# TITAN FuelMaster®

## Specifications

Specification	FM Cube	Standard	Advanced	Advanced	PRO
	1200L Only*	1225-2500L*	1225-2500L*	3500-9000L	3500-9000L
Green Door Lockable	•	•	•	•	
Red Door Lockable					•
72 lpm** Pump 230V	•	•	•	•	•
Digital Flowmeter			•	•	•
6m hose		•	•	•	•
4m hose	•				
Hose Holder Bracket			•	•	•
1" Suction Line	•	•	•	•	•
Auto Shut-Off Nozzle	•	•	•	•	•
Nozzle Holder	•	•	•	•	
Nozzle Holder c/w Auto Pump Switch					•
10 Micron Particle & Water Filter	•	•	•	•	•
2" BSP Coupling for filling	•	•	•	•	•
Drip tray in Cabinet				•	•
Spillstop Mechanical Overfill Protection	•	•	•	•	•
Motion Sensor Light			•	•	•
Junction Box for Wiring			•	•	•
Mechanical Level Clock Gauge	•	•	•		
Watchman Sonic Advanced Electronic Level Gauge			•		
Watchman Uni RX Electronic Level Gauge				•	
Watchman Access Fuel Management System					•
WAP (Watchman Anywhere PRO) Ready		•	•	•	•
Codes	0730000 (1200l)	1010086 (1225l) 1010087 (1300l) 1010088 (2500l)	1010092 (1225l) 1010093 (1300l) 1010094 (2500l)	1010095 (3500l) 1010096 (5000l) 1010097 (9000l)	1010119 (3500l) 1010120 (5000l) 1010121 (9000l)
Optional Extras					
100 lpm** Pump 230V				• 1010116 (3500l) 1010117 (5000l) 1010118 (9000l)	• 1010122 (3500l) 1010123 (5000l) 1010124 (9000l)
Retractable 8m hose reel				• 1010763 (3500l) 1010764 (5000l) 1010765 (9000l)	• 1010769 (3500l) 1010770 (5000l) 1010771 (9000l)
100 lpm** Pump 230V with Retractable 8m hose reel				• 1010766 (3500l) 1010767 (5000l) 1010768 (9000l)	• 1010773 (3500l) 1010774 (5000l) 1010775 (9000l)
WAP (Watchman Anywhere PRO)		• On Request	• On Request	• On Request	• On Request

\*FM Cube and Advanced specifications can also come with 12V (50lpm) or 110V (56lpm) pumps without light or Watchman Sonic Advanced (available on request). FM Standard can come with 12V (50lpm) pump (available on request).

\*\*Maximum across pump flow rate as defined by pump manufacturer. Actual flowrate will be less.

### Head Office

180 Gilford Road, Portadown,  
 Co. Armagh, BT63 5LF  
 United Kingdom  
 Email: tankinfo@kingspan.co.uk  
 Tel: +44 (0) 28 3836 4444

kingspan.com

### Ireland Office

Dundalk Road  
 Carrickmacross  
 Co. Monaghan  
 Email: tankinfo@kingspan.ie  
 Tel: +353 (0) 42 969 0022

