

DIESEL DISPENSING TANKS


AGRICULTURAL | COMMERCIAL | HAULAGE



Manufactured in the UK, our range of modern Bunded Diesel Dispensing Tanks are suitable for a variety of applications including agriculture, construction, mining and road haulage.







www.harlequinplastics.co.uk













Fuel Points & Fuel Stations

The Harlequin range of Bunded Diesel Dispensing Tanks are manufactured to exceed the most demanding technical, environmental and regulatory requirements. Available from 1300 right uptp 9,250 litre fuel station and fuel point models. Each tank is CE marked where appropriate with Declarations of Performance available on request. We also have a Transfuel range which you can find on our website - www.harlequinpalstics.co.uk.



1300 SLFS / SLFP

SLIMLINE

Length 2,300mm Width 950mm Height 1,850mm Capacity 1,344 litres Weight 175kg



1400 FS / FP

Length 1.610mm Width 1,570mm Height 1,880mm Capacity 1,498 litres Weight 150kg



2500 SLFS / SLFP

SLIMLINE

Length 2,550mm Width 1,385mm 1,985mm Height Capacity 2,530 litres Weight 210kg



2500 FS / FP

Length 2,060mm Width 2.020mm Height 1,880mm Capacity 2,571 litres Weight 200kg



3500 FS / FP

Length 2,200mm Width 2,200mm Height 2,060mm Capacity 3,553 litres Weight 250kg



5000 FS

Length 2,720mm Width 2,220mm Height 2,360mm Capacity 5,307 litres Weight 420kg



NEW



5000 FP AGRI

Length 2,360mm Width 2.360mm Height 2,210mm Capacity 5,314 litres Weight 350kg



7500 FS

Length 2,940mm Width 2,305mm Height 2,820mm Capacity 8,088 litres Weight 505kg



9250 FS

Length 3,140mm Width 2,510mm 2,820mm Height Capacity 9,328 litres Weight 600kg

OPTION 1

Fuel Station (FS)

Product Codes:

1300SLFS | 1400FS | 2500SLFS | 2500FS | 3500FS | 5000FS | 7500FS 9250FS

Harlequin Fuel Stations provide forecourt style refuelling convenience and come complete with a range of added value technologies as standard.

Standard Equipment with Fuel Stations:

- 56L/min 230V fuel pump (4)
- Mechanical flow meter for smaller FS up to 5000 litres (1)
- 10Micron particulate & water filter (5) 4m length, 1" delivery hose with auto-
- shut off nozzle 1300SLFS,1400FS
- 6m length; 1" delivery hose with autoshut off nozzle - 2500FS & above
- Bulkhead light (3)
- 2" BSP(M) fill point
- 4" lockable inspection cap
- Bund Monitor 5000, 7500 and 9250 FS
- Large lockable access door upto 5000FS
- Mechanical overfill prevention valve 7500 & 9250 FS
- LRC overfill prevention probe 5000, 7500 & 9250FS

- Electronic Level Gauge (2 or 6)
- Fuel Management System -7500FS & 9250FS - 240V. (8)
- Lockable equipment cabinet
- 7500 & 9250FS
- HVO Kit 5000, 7500 & 9250FS

Optional Equipment:

- 72L/min fuel pump (7)
- Fuel Management System upgrade available on smaller FS up to 5000 litres (8)
- 8m cabinet mounted auto hose reel avilable on 5000. 7500 and 9250 FS (g)
- HVO Kit Up to 3500FS

OPTION 2

Fuel Point (FP)

1300SLFP | 1400FP | 2500 SLFP | 2500FP | 3500FP | 5000FP AGRI

- 56L/min 230V fuel pump (1)
- 4m length; 1" delivery hose with
- 6m length; 1" delivery hose with
- 2" BSP(M) fill point
- Large lockable access door

- Mechanical flow meter (2)
- 10Micron particulate filter (3)
- Electronic Level Gauge (4 or 5)

*Warranty: 10 year conditional warranty only when product is registered on our website.

Standard & Optional Equipment:













7500 & 9250)















Please note: All tank capacities are brimful. All electrical installation work must be undertaken by a registered electrician.

& 9,250 - 240V)

(Only standard for 7500 (Optional on 5000,

For the latest product information give us a call or visit our website:

T 028 9261 1077 E info@harlequin-mfg.com www.harlequinplastics.co.uk

