

Key to Symbols: \triangle Lifting Point

\circ Hold-down strap rib locations where mechanical anchoring is required

| Manufacturing Joint

\circ BoQ's reference no.

| | | | | |
|--------------|------|-----|------------------------------------|-----|
| | | | | |
| Distribution | Date | Rev | Issued only for purpose indicated: | ** |
| | | | | BY: |

This drawing is confidential and must not be copied, reproduced or passed to a third party without written permission from
SPEL PRODUCTS

DIMENSIONS ARE SUBJECT TO DIMENSIONAL TOLERANCES. If critical, check physically prior to installation

Water table & Burial Depth: The customer must check tank specification is compatible with ground water table level (in winter) and burial depth. If in doubt refer to SPEL Data Manual Section 13 or contact SPEL Products Sales or Technical Department


Title: **SPEL 200 Series Washdown Separator Underground Tank**

Contract:

Capacity
2,000 Ltr.

Tank Specification
--

Laminate Specification
--



All sizes in mm
If in doubt ASK!

SPEL
Lancaster Road, Shrewsbury
Shropshire, SY1 3NQ, England
Telephone: +44 (0)1743 445200
www.spelproducts.co.uk

Drawn
Checked
Date
Scale 1:20 Sheet A3

TANK SERIAL No.
INTERNAL ORDER No.

Revision **A**