

TZST-13-S9, TZSTC-13-S9, TZSTBL-13-S9,  
TZST-13-S9/B36, TZSTC-13-S9/B36, TZSTBL-13-S9/B36

**SPECIFICATION**

- STAINLESS STEEL SHOWER COLUMN, GRADE #304
- ½" THERMOSTATIC VALVE
- 3 FUNCTIONS DIVERTER VALVE WITH HALF ZONES
- ASSEMBLED WITH STAINLESS STEEL BRAIDED HOSES
- SUPPLIED WITH ½" HI-FLOW HOSES
- ANTI-LIMESCALE SILICONE NOZZLES
- PRESSURE : MINIMUM 35 PSI, MAXIMUM 80 PSI
- ½" CONNECTION

**AVAILABLE OPTION**

- ADDITION OF A DIVERTER SPOUT (REF. MODEL TZST-13/B36)
- HAND SHOWER HOLDER SUPPORT REPLACED BY A SLIDING BAR

**AVAILABLE FINISH**

- BRUSHED STAINLESS STEEL : TZST-13
- MIRROR BLACK : TZSTBL-13
- CHROME : TZSTC-13

**ACCESSORIES**

ACCESSORIES	TZST-13-S9	TZSTC-13-S9	TZSTBL-13-S9	TZST-13-S9/B36	TZSTC-13-S9/B36	TZSTBL-13-S9/B36
SHOWER HEAD	PVTS-09-S	PVTS-09-S	PVTS-09-S	PVTS-09-S	PVTS-09-S	PVTS-09-S
HAND SHOWER	HS-204	HS-204	HS-204	HS-204	HS-204	HS-204
SUPPORT	HSHC-101	HSHC-101	HSHC-101	HSH-302	HSH-302	HSH-302
HOSE	SSHE-125	SSHE-125	SSHE-125	SSHE-175	SSHE-175	SSHE-175
DIVERTER SPOUT	N/A	N/A	N/A	R-36	R-36	R-36


**FLOW RATE**

THERMOSTATIC VALVE	30 L/MIN [7.9 GPM] @ 60 PSI
SHOWER HEAD	9.5 L/MIN [2.5 GPM] @ 60 PSI
HAND SHOWER	9.5 L/MIN [2.5 GPM] @ 60 PSI
JETS (2)	9.7 L/MIN [2.6 GPM] @ 60 PSI
DIVERTER SPOUT	17 L/MIN [4.5 GPM] @ 60 PSI
SPOUT	19.7 L/MIN [5.2 GPM] @ 60 PSI

**WARRANTY**

PRODUCTS COVERED BY A FULL LIMITED LIFETIME WARRANTY AGAINST ALL MANUFACTURING DEFECTS.

FOR MORE INFORMATION ABOUT THE PRODUCT, OR BEFORE PROCEEDING TO ANY INSTALLATION PLEASE CONSULT THE INSTALLATION MANUAL.



ASME 112.118.1 / CSA B125.1.

THE PRODUCT MAY VARY SLIGHTLY FROM ITS DIMENSION AND APPEARANCE.

REV.: 02/2018

