Date: April 2017

# caroma

# Somerton Smart Easy Height Elongated Bowl #829109W Tank #810788W

1.28/0.8 gpf (4.8/3 I) Water Saving Dual Flush High Efficiency Toilet (HET) Two Piece Ultra Low Flush Vitreous China Washdown Toilet





## **Somerton Smart Easy Height Elongated** 1.28/0.8 gpf (4.8/3 lpf) **Dual Flush HET**

#### Two Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet

### Bowl #829109W Tank #810788W



A modern concept close coupled 1.28/0.8 gpf (4.8/3 lpf), Somerton Smart Easy Height Elongated dual flush washdow toilet designed to provide a seat height of 17-1/2" (445mm) measured to the top of the toilet seat. The closet bowl has been designed with rough-in of 10" (255mm) to 12" (305mm) provided by an offset outlet connector option. The tank incorporates a high performance barrel type outlet valve which has been specially developed with the Easy Height Elongated bowl to ensure optimum reliable flushing performance. Due to the substantial water saving benefits achieved by the 1.28/0.8 gpf (4.8/3 lpf) dual flush system, the toilet is suitable for multi-purpose applications where water conservation is important. Important: The Somerton Smart Easy Height Elongated toilet will comply with the Americans with Disabilities Act when installed to Easy Height Standards for Accessible Design, Section 4.16 Water Closets. Further reference must be made to the relevant sections of Easy Height Standards for Accessible Design with current amendments to determine clear floor space, grab bar, and operation requirements.

Closet bowl: Somerton Smart Easy Height Elongated 1.28/0.8 gpf (4.8/3 lpf) dual flush washdown closet

bowl with box rim.

Outlet: Floor mounted suitable for connection to waste outlet with offset plastic outlet connector for

10"(255mm) to 12"(305mm) elongated outlet connection.

Tank: Somerton Smart Tank - has a free lifting lid and is suitable for domestic and light commercial application. 16" long toilet hose connector is included for easy installation.

Weight: Bowl Weight 57.2 lbs (26 kg) Tank weight 40 lbs (18.2 kg)

Water Control

10" (255mm)

Standard Bottom Entry Tank -- available as left hand inlet and incorporates a super quiet water Valve:

control assembly. Internal overflow only. 16" long toilet hose connector is included. The tank is fixed directly to the closet bowl with a robust base fixing system without the need

for wall fixing

The soft close detachable elongated top fixing seat is included: Code No. 326611W. Seat:

Colors:

Fixing:

Dimensions: All dimensions are in inches and millimetres and are subject to normal manufacturing variations.

Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

14-1/8"(360mm)1" (25mm) 0 (520mm) 140mm (765mm) 18-3/4" (475mm) 30-1/8" 10 5/8" (270mm) 14-3/16"(360mm) 18" (455mm min.) 1" (25mm) approx. (800mm) 2 31-1/2" (280)16-1/2''

Offset outlet Connector

Easy Height Elongated Tank	Code No. 810788W
Bowl	829109W









Note: All height dimensions to underside of closet bowl. Make allowance for bedding.

Closet bowl fixing: The closet bowl should be bedded with an approved silicon caulking.