



## MINI PEBBLE CONDENSATE REMOVAL PUMP



### DESCRIPTION

The Mini Pump is designed to be installed:

- above the false ceiling where possible
- in plastic conduit
- behind wall mounted evaporators

By connecting the drain hose to the reservoir and placing the pump drive unit within the evaporator, condensate water can be pumped to a height of 8 metres.

### IN THE BOX

- 1 x Pump
- 1 x Power cable
- 1 x Reservoir
- 1 x Inlet tube
- 1 x 16mm filter
- 1 x Breather tube
- 6 x Cable ties
- AV Pad

### SPECIFICATIONS

- Power: 230V AC 50-60Hz 16W
- High level safety switch with 3A volt-free wires and normally closed contacts
- Maximum water temperature: 40°C
- Class II appliance
- Non continuously rated
- Hall effect semi conductor level sensors
- Suction lift: 1m
- Outlet tube size: 6mm i/d
- Thermally protected
- 65mm (h) x 104mm (w) x 32mm (d) (pump)
- Weight: 0.25kg
- CE marked
- 1 year warranty

### PERFORMANCE

- Up to 13kW / 45,500Btu/h
- Water flow rate: 10L/hr at zero head
- Maximum recommended head: 8m
- 23dB(A) @ 1m

