

Section 1 - Identification of Chemical Product And Company

CDK STONE NZ Ltd 2/40 Canaveral Drive Rosedale Auckland NEW ZEALAND	Emergency Phone: 0800 764766 NZ Emergency Services: 111 Phone: 0800 803 932 Fax: +64 9 479 2424
--------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------

Substance:

Trade Name: **Lithofin Wax Off**

Product Use:

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as:

HAZARDOUS SUBSTANCE: according to the criteria of HSNO.
REGULATED under NZS5433:2007 Transport of Dangerous Goods on Land

HSNO Signal Word: DANGER

Emergency Overview

Physical Description & colour: Colourless liquid

Odour: Citrus

Hazard Classification:

Flammable Liquid	Category 3	3.1C
Acute Oral Toxicity	Category 5	6.1E
Acute Dermal Toxicity	Category 5	6.1E
Skin Effects	Category 2	6.3A
Eye Effects	Category 1	8.3A
Skin Sensitisation	Category 1	6.5B
STOT – SE RTI	Category 3	6.9
STOT – SE NE	Category 3	6.9
Aspiration	Category 1	6.1D
Acute Aquatic Hazard	Category 2	9.1B
Chronic Aquatic Hazard	Category 2	9.1B

Signal Word: DANGER

Hazard Statements:

H226	Flammable liquid and vapour
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H317	May cause an allergic skin reaction
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H334	May be fatal if swallowed and enters airways



H401 Toxic to aquatic life
H411 Toxic to aquatic life with long lasting effects



Precautionary Statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P240 Ground and bond container and receiving equipment
P241 Use explosion proof electrical/ ventilating/ lighting/ intrinsically safe equipment
P242 Use non-sparking tools
P243 Take action to prevent static discharge
P233 Keep container tightly closed

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection
P260 Do not breathe mists/ vapours/ sprays
P271 Use only outdoors or in a well-ventilated area
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

Response

P301+330+312 IF SWALLOWED: Rinse mouth. Call a POISON CENTRE/ doctor/ physician/ first aider if you feel unwell
P303+361+352 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with plenty of water and soap.
P332+313 If skin irritation occurs. Get medical attention
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing
P337+313 If eye irritation persists. Get medical attention
P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
P308+311 If exposed or concerned. Call a POISON CENTRE/ doctor/ physician/ first aider

P370+378 In case of fire use alcohol resistant foam or normal protein foam to extinguish

Storage

P403+235 Store in a well-ventilated place. Keep cool
P405 Store locked up

Disposal

P501 Dispose of content/ container to an authorised hazardous or special waste collection point in accordance with local regulation

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc. %
Hydrocarbons C ₉₋₁₀ n-alkanes, isoalkanes, cyclics (2-25%)	64742-82-1	60 – 70 %
Hydrocarbons C ₉ aromatics	64742-95-6	30 – 40 %
Orange, sweet, ext.	8028-48-6	1 – 10 %
Alcohols, C ₉₋₁₁ iso, C ₁₀ rich, ethoxylated	78330-20-8	1 – 10 %

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non-hazardous ingredients are also possible.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 0800 764766 from anywhere in New Zealand (13 1126 in Australia) and is available at all times. Have this SDS or product label with you when you call.

Eye Contact:	Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact:	Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation:	remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion:	If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness, i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. Avoid giving milk or oils. Avoid giving alcohol. If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.
Note to Physician:	Treat symptomatically

Section 5 - Fire Fighting Measures

Extinguishing Media:	Preferred extinguishing media are water spray or fog, dry chemical, BCF or foam
Fire and Explosion Hazards:	Liquid and vapour are flammable. Moderate fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Moderate explosion hazard when exposed to heat or flame. Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO).
Fire Fighting:	Alert Fire & Emergency New Zealand and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Fight fire from a safe distance, with adequate cover. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot. Equipment should be thoroughly decontaminated after use
Fire Decomposition:	Carbon monoxide (CO), Carbon dioxide (CO ₂) and other pyrolysis products typical of burning organic material.

Section 6 - Accidental Release Measures

Minor Spills:	Remove all ignition sources. Clean up all spills immediately Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb small quantities with vermiculite or other absorbent material. Wipe up Collect residues in a flammable waste container.
Major Spills:	Clear area of personnel. Alert Fire & Emergency New Zealand and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment as required. Prevent spillage from entering drains or water ways. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal. Wash area and prevent

runoff into drains or waterways. If contamination of drains or waterways occurs, advise emergency services.

Section 7 - Handling and Storage

Handling: Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Avoid all personal contact, including inhalation. Wear protective clothing when risk of overexposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights or ignition sources. Avoid generation of static electricity. DO NOT use plastic buckets. Earth all lines and equipment. Use spark-free tools when handling. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

Storage: Store in original containers in approved flammable liquid storage area. Store away from incompatible materials in a cool, dry, well-ventilated area. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. No smoking, naked lights, heat or ignition sources. Storage areas should be clearly identified, well illuminated, clear of obstruction and accessible only to trained and authorised personnel - adequate security must be provided so that unauthorised personnel do not have access. Store according to applicable regulations for flammable materials for storage tanks, containers, piping, buildings, rooms, cabinets, allowable quantities and minimum storage distances. Use non-sparking ventilation systems, approved explosion proof equipment and intrinsically safe electrical systems. Have appropriate extinguishing capability in storage area (e.g. portable fire extinguishers - dry chemical, foam or carbon dioxide) and flammable gas detectors. Keep adsorbents for leaks and spills readily available. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. Packing as supplied by manufacturer. Plastic containers may only be used if approved for flammable liquid. Check that containers are clearly labelled and free from leaks.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

Exposure limits

CAS no.	Substance or ingredient	WES-TWA	WES-STEL
64742-82-1	Hydrocarbons C9-10 n-alkanes, isoalkanes, cyclics (2-25%)	525 mg/m ³ 100 ppm	

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5-day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Engineering Controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. For flammable liquids and flammable gases, local exhaust ventilation or a

process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh

Personal Protective Equipment

Eye Protection:



Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly

Skin Protection:



Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber Overalls. PVC Apron. PVC protective suit may be required if exposure severe.

Protective Material Types:

We suggest that protective clothing be made from the following materials:

PVA

Teflon

Respirator:



Type A of sufficient capacity

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Colourless liquid
Odour:	Citrus
pH:	not applicable
Vapour Pressure:	no data
Relative Vapour Density:	not available
Viscosity	12 s ISO 4mm
Boiling Point:	167 °C
Volatiles:	no data %
Water Solubility:	emulsifiable
Freezing/Melting Point:	-13 °C
Specific Gravity:	0.8 g/ml
Flashpoint	43 °C
Auto ignition temp:	no data °C
Evaporation Rate:	not available
Coeff Octanol/water distribution	no data

Section 10 - Stability and Reactivity

Stability	Product is considered stable
Conditions to Avoid:	Avoid contact with ignition sources
Incompatibilities:	Segregate from alkalis, oxidising agents and chemicals readily decomposed by acids i.e. cyanides, sulfides, carbonates. Avoid reaction with oxidizing agents, i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Inhaled:

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhalation hazard is increased at higher temperatures. Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and lightheadedness. Low molecular weight (C2-C12) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor. Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal. On exposure to mixed trimethylbenzenes, some people may become nervous, tensed, anxious and have difficulty breathing. There may be a reduction red blood cells and bleeding abnormalities. There may also be drowsiness. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Heart stoppage may result from cardiovascular collapse. A slow heart rate and low blood pressure may also occur. Alkylbenzenes are not generally toxic except at high levels of exposure. Their breakdown products have low toxicity and are easily eliminated from the body.

Ingestion

Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. Accidental ingestion of the material may be damaging to the health of the individual. Ingestion of petroleum hydrocarbons can irritate the pharynx, oesophagus, stomach and small intestine, and cause swellings and ulcers of the mucous. Symptoms include a burning mouth and throat; larger amounts can cause nausea and vomiting, narcosis, weakness, dizziness, slow and shallow breathing, abdominal swelling, unconsciousness and convulsions.

Skin Contact

Skin contact with the material may be harmful; systemic effects may result following absorption. The material may accentuate any pre-existing dermatitis condition. Open cuts, abraded or irritated skin should not be exposed to this material. Entry into the blood-stream, through for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives. Aromatic hydrocarbons may produce sensitivity and redness of the skin. They are not likely to be absorbed into the body through the skin, but branched species are more likely to. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

Eye Contact

If applied to the eyes, this material causes severe eye damage. Direct eye contact with petroleum hydrocarbons can be painful, and the corneal epithelium may be temporarily damaged. Aromatic species can cause irritation and excessive tear secretion. The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated.

Chronic Health Effects

Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Repeated application of mildly hydrotreated oils (principally paraffinic), to mouse skin, induced skin tumours; no tumours were induced with severely hydrotreated oils. There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. A number of common flavor and fragrance chemicals can form peroxides surprisingly fast in air. Antioxidants can in most cases minimize the oxidation. Fragrance terpenes are easily oxidized in air. Non-oxidised forms are very weak sensitizers; however, after oxidation, the hydroperoxides are strong sensitizers which may cause allergic reactions. Autooxidation of fragrance terpenes contributes greatly to fragrance allergy. There is

the need to test for compounds the patients are actually exposed to, not only the ingredients originally applied in commercial formulations. d-Limonene may cause damage to and growths in the kidney. These growths can progress to cancer. Peroxidisable terpenes and terpenoids should only be used when the level of peroxides is kept to the lowest practicable level, for instance by adding antioxidants at the time of production. This should be less than 10 millimoles of peroxide per litre. This is because peroxides may have sensitizing properties. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.

TOXICITY AND IRRITATION

Ingredient	Oral LD ₅₀	Dermal LD ₅₀	Inhalation LC ₅₀
Hydrocarbons C9-10 n-alkanes, isoalkanes, cyclics (2-25%)	>4500 mg/kg		
Hydrocarbons C ₉ aromatics	>4500 mg/kg		7331 mg/L/8h
Orange, sweet, ext.	>5000 mg/kg	>5000 mg/kg	

Section 12 - Ecological Information

Harmful to aquatic organisms, Toxic top aquatic life with long lasting effects

This material and its container must be disposed of as hazardous waste.

Avoid release to the environment.

Ingredient	Fish	Crustacea	Algae
Hydrocarbons C9-10 n-alkanes, isoalkanes, cyclics (2-25%)	LC ₅₀ 96hr 4.1 mg/L	EC ₅₀ 48hr 4.5 mg/L	EC ₅₀ 72hr 13 mg/L NOEL 72hr 0.1 mg/L
Hydrocarbons C ₉ aromatics	LC ₅₀ 96hr 4.1 mg/L	EC ₅₀ 48hr 3.2 mg/L	EC ₅₀ 72hr >1 mg/L NOEL 72hr 0.1 mg/L
Orange, sweet, ext.	LC ₅₀ 96hr 0.32 mg/L	EC ₅₀ 48hr 0.45 mg/L NOEC 48hr 0.48 mg/L	EC ₅₀ 72hr 0.36 mg/L

	Persistence H ₂ O/ Soil	Persistence Air	Bioaccumulation	Mobility
Orange, sweet, ext.	HIGH	HIGH	HIGH	LOW

Section 13 - Disposal Considerations

Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container cannot be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product.

DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible or consult manufacturer for recycling options. Consult Land Waste Authority for disposal. Bury or incinerate residue at an approved site. Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled. The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. Only dispose to the environment if a tolerable exposure limit has been set for the substance. Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

Section 14 - Transport Information



HAZCHEM

3[Y]

Land Transport UNDG

Class or division 3
 Subsidiary Risk None
 UN Number **1993**
 UN Packing Group III
 Special Provisions 223 274
 Limited Quantity 5 Lt
 Shipping Name FLAMMABLE LIQUID N.O.S

Air Transport IATA

ICAO/IATA Class 3
 ICAO/IATA Subrisk None
 UN/ID Number **1993**
 ERG Code 3L
 Packing Group III
 Special provision A3
 Cargo only
 Packing instructions 366
 Maximum Qty/pack 220 Lt
 Passenger and Cargo
 Packing instructions 355
 Maximum Qty/pack 60 Lt
 Passenger & Cargo Limited Quantity
 Packing instructions Y344
 Maximum Qty/pack 10 Lt
 Shipping Name FLAMMABLE LIQUID N.O.S

Marine Transport IMDG

IMDG Class 3
 IMDG Subrisk None
 UN Number **1993**
 UN Packing Group III
 EmS Number F-E S-E
 Special provisions 223 274 955
 Limited quantities 5 Lt
 Marine pollutant Yes
 Shipping Name FLAMMABLE LIQUID N.O.S

Section 15 - Regulatory Information

HSNO Approval: **HSR002528** **Cleaning Products (Flammable)**

Group Standard conditions and other regulations:

Condition	Requirement
SDS	Safety data sheet must be available to a person handling the substance within 10 minutes.
Emergency plan	Required when quantities exceed 500 Lt
Certified handler	Not required
Tracking	Not applicable

Bunding and secondary containment	Required dependent on pack size and total volume
Signage	Required when present in quantities exceeding 100 Lt
Location Compliance Certificate	Required when in excess of 500Lt in containers of greater than 5Lt capacity, else greater than 1500Lt containers of upto and including 5Lt capacity, else greater than 250Lt in open containers. Quantity ratio applies
Hazardous Area	Required as per AS/NZS 60079.10
Fire extinguisher	2 required when quantities exceed 250 Lt

National Inventories

Australia	AICS	Y
Canada	DSL	Y
Canada	NDSL	N
China	IECSC	Y
Europe	EINEC/ELINCS/NLP	N
Japan	ENCS	N
Korea	KECI	Y
New Zealand	NZIOC	Y
Philippines	PICCS	Y
USA	TSCA	Y
Taiwan	TCSI	Y
Mexico	INSQ	Y
Vietnam	NCI	Y
Russia	ARIPS	Y

Section 16 - Other Information

Revision History

August 2020

Initial Preparation

Acronyms:

CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially fire-fighters
HSNO	Hazardous Substances & New Organisms Act
IARC	International Agency for Research on Cancer
ICAO Technical Instruction	International Civil Aviation Organization Technical Instructions
IMDG Code	International Maritime Dangerous Goods Code controlled by the International Maritime Organisation (IMO)
LC₅₀	Lethal concentration 50% - concentration fatal to 50% of a population
LD₅₀	Lethal dose 50% - concentration fatal to 50% of a population
NZS 5433	New Zealand Standard 5433 (Standard for the Transport of Dangerous Goods on Land)
SDS	Safety Datasheet
STEL	Short Term Exposure Limit
TWA	Time Weighted Average (typically measured as 8-hours)
UN Number	United Nations Number
WES	Workplace Exposure standard

References

Chemical properties and HSNO classifications derived from the New Zealand chemical classification information database (CCID).

www.epa.govt.nz

Workplace exposure limits derived from Workplace Exposure Standards and Biological Exposure Indices 11th Edition (November 2019).



Safety Data Sheet

Page 10 of 10

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other material or in any process, unless specified in the text.

This SDS was prepared by Collievale Enterprises Ltd in accord with the Hazardous Substances (Safety Data Sheets) Notice 2017
<http://www.collievale.com> Phone +64 7 5432428

End of SDS