



CHRISTO-LUBE[®] MCG 200A

CHRISTO-LUBE[®] MCG 200A is a fluorinated polysiloxane grease thickened with PTFE which operates under extreme temperature conditions. This non-migrating fluorosilicone lubricant is clean room compatible and is especially useful in lubricating various types of bearing, gears and rails found in semiconductor manufacturing environments.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Fluorosilicone
Temperature Service Range (°C)		-30 to 230
GREASE CHARACTERISTICS		
Thickener		PTFE
Color		Yellow
Appearance		Smooth
NLGI Grade		2
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	265-295
	Worked	60X 265-295
Oil Separation (ASTM D6184)	24h at 149°C	10% max.
Evaporation (CTM-1)	24h at 149°C	3% max.
Water Washout (ASTM D1264 / DIN 51807-T2)	60 min at 79°C	0.50%
Four Ball Wear (ASTM D2266 / DIN 51350-T5)	60 min 1200 RPM 75°C 40kg _f	0.73mm
	Dynamic Coefficient of Friction (steel on steel)	0.079
Specific Gravity (CTM-2)	25°C	1.97

Engineered Custom Lubricants

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.