

ANTUNES WATER SOFTENER SYSTEM

Hard water can lead to a variety of issues in your home, ranging from mild annoyances like stiff, dingy laundry and difficulty getting dishes clean to bigger impacts like scale buildup, higher energy bills and poor appliance performance.

The Antunes Water Softener is available in two models, each of which leverages ion exchange to convert calcium and magnesium in your water supply to harmless sodium, giving you softer water.



WATER SOFTENER SYSTEM

PART NUMBER	9720010	9720011
MODEL	WSS-0948-R	WSS-1252-R
FLOW RATE	10 gpm (37.9 lpm)	11.5 gpm (43.5 lpm)
PRESSURE DROP @ RATED FLOW RATE	15 gpm (56.8 lpm)	15 gpm (56.8 lpm)
PRESSURE DROP @ RATED FLOW RATE	15 gpm (56.8 lpm)	15 gpm (56.8 lpm)
DRAIN FLOW RATE	2 gpm (7.6 lpm)	3.5 gpm (13.2 lpm)
SOFTENER DIAMETER	9" (23 cm)	12" (30.5 cm)
SOFTENER HEIGHT	57" (145 cm)	63" (160 cm)
SOFTENER OPERATING WEIGHT	125 lbs (57 kg)	220 lbs (91 kg)
SOFTENER TANK SIZE	9" x 48"	12" x 52"
BRINE TANK DIAMETER	18" (45.7 cm)	18" (45.7 cm)
BRINE TANK HEIGHT	36" (91.4 cm)	36" (91.4 cm)
BRINE TANK OPERATING WEIGHT	200 lbs (100 kg)	200 lbs (100 kg)
RESIN VOLUME (CUBIC FEET)	1	2
RATED CAPACITY (GRAINS @ LBS OF SALT)	18,000 @ 4.0 27,800 @ 9.0 31,500 @ 15.0	35,900 @ 8.0 55,700 @ 18.0 63,000 @ 30.0
RATED EFFICIENCY (GRAINS/LB. SALT @ LBS. OF SALT)	4,490 @ 4.0	4,490 @ 8.0
VOLTS	120	120
HERTZ	50/60	50/60
WATTS	40 VA	40 VA
AMPS	0.33	0.33
OPERATING PRESSURE (PSI)	20-125	20-125
OPERATING TEMPERATURE	34-110°F (1.1-43.3°C)	34-110°F (1.1-43.3°C)
INLET	1" NPT Male	1" NPT Male
OUTLET	1" NPT Male	1" NPT Male
DRAIN	½" ID HOSE	½" ID HOSE