



NHPL-1825-UNC

**Heater Proofers - Non-Insulated
Universal Runner
100% Pre-Tested Electrical Assembly**

- Non-insulated - Heavy duty aluminum construction.
- Forced air design provides even heat distribution.
- Removable chrome pan slides for variable spacing and for easy cleaning. Wire slided can be adjusted on 2" increments. Ships with 25 pan slide sets.
- 5" polyurethane plate casters for easy maneuverability and stability. Front casters are provided with brakes.
- Easy dual proof/heat control:
 - "Proof/humidity" mode: Up to 95% RH at 110°F (43°C)
 - "Heat" mode: Maximum Temperatures up to 180°F (82°C)
- Full length clear door opens 90 degrees.
- Field reversible door for right or left hanging is standard. Magnetic door latch for keeping door closed during transport. Easy pull handle for opening.
- Wire slided can be adjusted on 2" increments.
- Slides accommodate standard steam pans.
- Control drawer is removable for quick and easy cleaning and maintenance.
- Drip Trough catches condensation. Internal water pan collects condensation or is used in proofer mode.
- All controls are accessible without opening cabinet door. Easy to read real time LED thermometer display.
- Pan Capacity: 28 - 18" x 26" pans
- Corner bumpers provide protection to unit, associates and fixtures.

Electrical specifications:

- 120 Volt-60 Hz, NEMA 5-15P
- 1440 Watts: 14.0 AMPS - Plug into any standard 110 outlet.



Adjustable Universal Runners
Holds a variety of pan configurations.

Option: Additional runner slide (1)
NHPL-1825-UN-Runner
(657150)

Magnetic Door Latch



Field Reversible Door Mount

Model Number	Order#	Overall Dimensions						Approx. Ship Wt	
		Width		Length		Height		(lb)	(kg)
		(in)	(mm)	(in)	(mm)	(in)	(mm)		
NHPL-1825-UNC	684641	24	610	32	813	70	1,778	235	106

Caster Information

- Swivel Plate Caster with 5" Polyurethane Wheel 738A (128784)
- Swivel Plate Caster with 5" Polyurethane Wheel & Brake 738ABK (204185)
- 5" Polyurethane Wheel 7112 (122180)

Freight Class: 100

