

FEDERAL INDUSTRIES

A Standex Company 215 Federal Avenue Belleville, WI 53508-9201

Phone: 800-356-4206 Fav: 608-424-3234

1 ux. 000 -	727 3237
Email: ge	ninfo@federalind.com
Website:	www.federalind.com

Project Name:	AIA#
Item #:	
Model #: Qty:	SIS#
Approval:	

SIGNATURE SERIES REFRIGERATED COUNTER TOP MERCHANDISER

COUNTER TOP SIGNATURE SERIES REFRIGERATED REAR MOUNT

MODEL	LENGTH (Includes End Panels)
□ CRR3628	36 x 29.7 x 27.83 (in)
	914 x 754 x 707 (mm)
□ CRR4828	48 x 29.7 x 27.83 (in)
	1219 x 754 x 707 (mm)

The Signature Series counter top merchandiser combines attractive curved glass styling and merchandising flexibility. Designed for continuous case line-ups. Cases are available in lengths of 3' and 4'.





OPTIONAL ACCESSORIES

- ☐ Glass Shelves
- □ Reflective Ends
- □ Reflective Rear Doors
- □ Remote Refrigeration
- ☐ Chocolate Package

REFRIGERATED BOTTOM MOUNT

MODEL	LENGTH (Includes End Panels)
□ CRB3628	36 x 29.7 x 25.12 (in)
	914 x 754 x 638 (mm)
□ CRB4828	48 x 29.7 x 25.12 (in)
	1219 x 754 x 638 (mm)

STANDARD FEATURES

Model Features

- Curved glass styling.
- Tempered thermopane front glass. Acrylic end panels.
- Removable sliding rear doors, shelf lights, shelf supports, and shelves.
- Removable, scratch-resistant, rustproof black display
- Easily accessible light switch and adjustable temperature control.
- Average case temperature of 38° F to 40° F is maintained.
- Black painted metal and stainless construction. Black
- Designed for continuous line-ups.
- Cord and plug (NEMA 5-15P).
- Installation Flexibility
- Set directly on counter with condensing component mounted on rear (CRR Models).
- Recessed 3" in the counter with condensing component mounted underneath (CRB Models).

Refrigeration

- Condensate evaporator provided for a totally selfcontained system.
- Oversized coil and low-velocity fan system maintains high humidity and product freshness.
- Average case temperature of 38° F (3.3° C) to 40° F (4.4° C) is maintained.
- Thermometer.
- 134A Refrigerant.

• Adjustable black wire shelves. Shelves are adjustable up and down and can also be tilted in two positions. Two tiers.

Lighting

• 3500K LED top light and shelf lights.

Agency Approvals

• UL Safety and UL Sanitation Listed.









AIA#

SIGNATURE SERIES REFRIGERATED COUNTER TOP MERCHANDISER

SIS#


Product Specifications


Intended Environment: Type I - Designed to operate in maximum ambient conditions of 75°F (24°C) and 55% relative humidity unless noted otherwise in system information below.

İ	Zone	Intended Product To Be Displayed	Avg Prod Temp °F/°C
I	All	Packaged Refrigerated Products	38°F / (3.3°C)

DIMENSION: xx"/(mm)

DIMENSION TOLERANCE +/- 0.19 (4.8)





MODEL	DIMENSIONS*			SHIPPING WHT		SELF-CONTAINED	REMOTE	
MODEL	L	D	Н1	UNITS	LBS	KILO	120/60/1	120/60/1 REAR MOUNT
REAR MOUNT	REAR MOUNT							
CRR3628	36	29.7	27.83	in.	430	195	8.1 AMPS	1.5 AMPS
CKK3628	914	754	707	mm.				
CDD4020	48	29.7	27.83	in.	500	227	8.3 AMPS	1.5 AMPS
CRR4828	1219	754	707	mm.				
воттом моинт								
CRB3628	36	29.7	25.12	in.	430	0 195	8.1 AMPS	3.6 AMPS
	914	754	638	mm.				
CDD4020	48	29.7	25.12	in.	500	227	8.3 AMPS	3.8 AMPS
CRB4828	1219	754	638	mm.				

- * Height above counter
- If a GFCI circuit is required, a GFCI Breaker Must be used instead of GFCI receptacle.
- Refrigerated cases are designed to operate in a maximum of 75°F (24°C) ambient and 55% relative humidity.
- Due to continuing engineering improvements, specifications are subject to change without notice.







FEDERAL INDUSTRIES

A Standex Company

215 Federal Avenue, Belleville, WI 53508-9201

PHONE: 800-356-4206 FAX: 608-424-3234

E-MAIL: geninfo@federalind.com WEBSITE: www.federalind.com

