

#### **FEDERAL INDUSTRIES**

A Standex Company

215 Federal Avenue Belleville, Wisconsin 53508-9201

**Phone:** 800-356-4206 **Fax:** 608-424-3234

**Email:** Geninfo@Federalind.com **Website:** Federalind.com

Project Name:	AIA#
Item #:	
Model #: Qty:	SIS#
Approval:	

# Refrigerated Self-Serve Counter Top Merchandiser

Designed to drive impulse sales of packaged food where retail space is limited.



Shown with optional stainless exterior and interior finish

# **OPTIONAL ACCESSORIES**

- ☐ Stainless Steel Exterior and Interior (Including Shelving)
- ☐ White Exterior and Interior (Including Shelving)

\*Additional options available on the website and price list.











# WARRANTY\* One year Parts and Labor 2nd thru 5th year part only service compressor [U.S.A. and Canada] Wo

Note: Information is subject to change at any time. Visit www.federalind.com for the most current specs.

MODEL	DIMENSION (Includes End Panels)			
☐ TSSM2454	24.71 x 28 x 53.71 (in) 614 x 723 x 1364 (mm)			

### **STANDARD FEATURES**

#### **Model Features**

- Black exterior and galvanized steel back
- Stainless steel slanted display deck with 11/8" (28 mm) price tag molding
- Black interior
- Side air intake and top discharge
- Condenser air filter cleaning indicator light
- Easy to remove washable condenser air filter
- Energy-saving night curtain
- Black end panels with insulated glass panes, argon filled
- (7', 2100mm) Cord and plug, NEMA 5-15P 90° Plug
- Insulated with high-density urethane foam

#### Refrigeration

- Condensate pump provided with field installed (25', 7620mm) tubing with sides and rear exit option
- Electronic temperature controls with on demand defrost
- Refrigeration control maintains 38°-40° F / 3.3°-4.4°C case temperature.
   Note: Case temperature will vary if the air curtain is disrupted.
- Coated Evaporator Coil
- Thermometer, bulb and capillary, 4", (102mm) long
- · R404A refrigerant

#### Shelving

 Two tiers of adjustable black shelves with 11/8" (28 mm) price tag molding. Shelves can be flat or slanted downwards at 10°

#### Lighting

- 3500K LED top light and LED Shelf lights
- IP65 rated

## **Agency Approvals**

- UL, C-UL and UL Sanitation listed to NSF-7, Type I conditions
- DOE 2017 compliant

AIA#

## Refrigerated Self-Serve Counter Top Merchandiser

SIS#


**Product Specifications** 

Intended Environment: Type I - Designed to operate in maximum ambient conditions of 75°F (24°C) and 55% relative humidity unless noted otherwise in system information below.

-			
Zone Intended Product To Be Displayed		Avg prod temp °F / °C	
All	Packaged Refrigerated Products	38°F/(3.3°C)	

DIMENSION: xx"/(mm)

**DIMENSION TOLERANCE+/-0.25(6.4)** 



MODEL	DIMENSIONS			SHELVES	SHIPPING WEIGHT		SELF CONTAINED		STANDARD NEMA PLUG	Н.Р	
	L	D	н	UNITS	SHELVES	LBS	KILO	VOLTAGE	AMPS	CONFIG (SC)	п.Р
	24.17	28.45	53.71	in	2 (15.2 x 22) in (386 x 559) mm	250 113		100/10/1		5 455	4 (0 115
TSSM2454	614	723	1364	mm			120/60/1	MAX FUSE 20	5-15P	1/2 HP	

- Case temperature will vary if the air curtain is disrupted.
- Refrigerated cases are designed to operate in a maximum of 75°F (24°C) ambient and 55% relative humidity.
- Due to continuing engineering improvements, specifications are subject to change without notice.
- Condensate Pump Drain Hose must be routed to a remote drain at installation.









Phone: 800-356-4206 Fax: 608-424-3234

**Email:** Geninfo@Federalind.com **Website:** Federalind.com