

Project Name:		AIA#;
Model #:	Location:	
SIS#:	Item #:	Quantity:

V-Series 30 Qt. Mixer

The kitchen workhorse, for a wide range of heavy-duty mixing applications.



MODELS

Design of Managers

V30 30 qt. Floor

STANDARD FEATURES

- Stainless steel top cover, planetary cover, bayonet shaft, bowl guard and legs
- IP32 rated
- Powerful 2 HP motor with variable speed drive and wide agitator speed range from 57 RPM to 311 RPMs
- #12 attachment hub with 198 RPM speed
- No bowl adapters needed to downsize bowls
- Hydraulic damper for easier bowl lowering, and single lever manually raises bowl and locks into position
- Front-mounted controls with 90-minute digital timer and emergency stop
- Durable powder coated finish used on legs and outside surfaces not constructed of stainless steel
- High torque transmission
- Permanently lubricated planetary head and attachment hub case
- Grease lubricated, anti-friction ball bearings
- Locking pin on tools instead of shaft
- Patent-pending interlock automatically turns the mixer off if bowl guard is opened or bowl is lowered
- Overload protection and no voltage release
- Non-skid rubber feet
- 6 foot cord
- cETLus and NSF listed
- Made in Denmark

STANDARD ACCESSORIES

- Stainless steel dough hook
- Stainless steel wire whip
- Stainless steel flat beater
- Stainless steel bowl
- Stainless steel ingredient chute

WARRANTY

Two-year parts & labor limited warranty

OPTIONAL ACCESSORIES/ATTACHMENTS

- 16 qt. bowl and accessories
- Bowl scraper 16 qt. or 30 qt. options
- Bowl truck

To select options see back



Intertek

ETL listed Conforms to UL Std 763 Certified to CSA Std C22.2 No. 195


Approved by: ____

Date:

....

NSE

2215 East River Rd., Davton, OH 45439 | 800-222-1138 | www.varimixerusa.com



SPECIFICATIONS							
Model	Motor	Volts	Amp	Plug Type	Mixing Speeds	Hub Speeds	IP Rating
V30	2 HP	120/60/1	20		57 - 311 RPMs	198 RPMs	IP32

Delivered without plug. Other voltages upon request with 6 to 8 week lead time.

Reinforced carton for shipping. This product ships on a pallet. See dimensions below.							
Model	Overall Dimensions	Net Wt.	Shipping Dimensions	Ship Wt.	Freigh	nt Class	
V30	21.2" W x 37" D x 47.63" H (54 cm x 94 cm x 121 cm)	374.8 lbs. (170 kg)	32" W x 49" D x 61" H 525 lbs. (81.3 cm x 124.4 cm x 154.9 cm) (238.14 kg)		85 55 CU ft.		
OPTIONA	L/ADDITIONAL ACCESSORIES			Product	Attachment	Capacity	
UBOWL16-30 16 qt. bowl VTRUCK-30 Bowl truck		wl truck	Mashed Potatoes	Whip / Beater	26 lbs.		

WHOOK16-30 16 qt. hook	Strain Strain Strain Action and the Action Strain Action and Action Strain Action Action Strain Action Action Strain Action Acti	Whipped Cream	Whip	7 gts.
UWHIP16-30 wire whip VBEAT16-30 16 qt. flat beater	XSVGH-XSP Housing & slicer hub assembly L00783 Strip cutter attachment	Bread Dough (60% AR)	Hook	35 lbs.
VSCRP16-30 16 qt. scraper	L00670 Meat tenderizer attachment	Pizza Dough (50% AR)	Hook	30 lbs.
USCRP-30 30 qt. scraper		Pancake Batter	Whip / Beater	14 qts.
UHDWHIP-30 30 qt. heavy-duty whip				
VWINGWHIP-30 30 qt. wing whip				

Heavy-duty 30 qt. mixer with 2 HP motor, high-torque transmission and variable speed drive from 57 to 311 RPMs. IP32 rated. Mixer has front-mounted control panel with timer and emergency stop. Mixer has grease lubricated, anti-friction ball bearings and permanantly lubricated planetary head & attachment hub case. Overload protection, interlocked bowl and bowl guard and no volt release. cETLus and NSF listed. 2-year parts & labor limited warranty.

2215 East River Rd., Moraine, OH 45439 | 800-222-1138 | www.varimixerusa.com