

CRAWLSPACE SUMP PUMP KIT YC-CIS33V-BCFA

EASY-TO-FIT PUMPS FOR HARD-TO-FIT SPACES

Contains

⅓ HP AC Pump (CIS-33V)

Check Valve (PS-CVWRU)

Water Alarm (PWA2) with Water Sensor (PS-WS)

Single Sump Base (SF1A)

Crawlspace Basin with Cover (YC-CSB1315)

Quick and Easy

Compact, heavy-duty basin fits easily through a crawlspace door, with no massive hole to dig.







Industrial Grade for the Residential Market

YourCrawlspace.com

843-287-9871




Pump Features and Construction

- Cast-iron sump/effluent pump
- ⅓ HP energy-efficient Permanent Split Capacitor (PSC) motor
- Built-in vertical float switch
- Cast-iron vortex impeller
- Upper and lower ball bearings
- · Carbon ceramic plus Buna N shaft seals
- · Thermally protected
- Stainless-steel fasteners
- Pumps solids up to ½ inch
- Removable strainer
- 10-foot power cord
- 3-year limited warranty

Pump Specifications Model CIS33V

Motor HP	⅓ HP
GPM @ 10 ft	53
GPH @ 10 ft	3,200
Discharge	1.5 in/3.8 cm
Amps @ 10 ft	5
Weight	21.1 lbs/9.6 kg
Width	9 in/22.9 cm
Depth	6.5 in/16.5 cm
Height	11.75 in/29.8 cm
Activation Level	8.9 in/22.5 cm
Deactivation Level	4 in/10.2 cm

Pump Flow Chart



Water Alarm Features Model PWA2 & PS-WS



- Minimize the risk of water damage
- 110 db alarm will sound when water lifts the Water Sensor or as little as ¹/₃₂" of water reaches the sensor pads on the bottom of the alarm
- Includes water sensor with 'L' bracket and hose clamp
- Includes 6 feet of wire on the sensor pads for remote monitoring
- Wires can be extended to hundreds of feet



Sump Foot Specifications Model SF1A

- · Keeps pumps raised above dirt and debris
- Made of high-impact polypropylene
- 7 ¼" W x 9 ¾" L x 2" H



Crawlspace Basin Specifications

- 12.5" X 15" perforated sump pump pit
- Includes 2-hole cover with 1.5" x 2" opening
- Made from structural foam material for a durable, long-lasting product
- · Capacity: 7.3 U.S. gallons

Available from:

YourCrawlspace.com

843-287-9871