

# NOUVEAU 6 CLICK | Technical Data

## PRODUCT INFORMATION:

Plank Size (Length x Width x Height)	Edge Profile	Finish	Construction		Installation	Species
6-1/2"x1/2"x RL16"-47"	4 Sides Bevel	UV Finish	Multi Layer Ply Core	5-10°	Float&click(Uniclic)	European Oak, Hickory

### WARRANTY:

### PACKAGING:

### PALLET:

Residential		Planks/Carton		Carton Dimensions (Length x Width x Height)		Cartons/ Pallet	
30	5	8	29.35SQFT	L2145 x W335x H56	21.44KG	51	1526.25SQFT

## Dimensional Characteristics and Limit Deviations

Deviation	Description	Limit	Result
Deviation	Deviation of Length	±0.1% of length up to 1mm maximum	Pass
	Deviation on Width	±0.20mm	Pass
	Deviation of Thickness	±0.25mm	Pass
Bow	Convex	≤1.0%	Pass
	Concave	≤0.50%	Pass
Cup	Convex	≤0.20%	Pass
	Concave	≤0.15%	Pass
	Height Difference	≤0.20mm	Pass
	Opening Between Elements (Gap)	≤0.15mm	Pass
	Spring	≤0.3mm	Pass
	Straightness	≤0.2mm	Pass
	T&G or Click System	Perfectly Match master Samples	Perfect Match
	Bevel	Perfectly Match master Samples	Perfect Match

EN 13647-2011  
ANSI-HPVA EF 2012

Per Product Specification of BMCI

## TESTING:

Reference	Standard	Test Request	Result
Abrasion Resistance	ASTM D4060	≥130 cycles	Pass
Adhesion	ASTM D3359	≥4B	Pass
Moisture Content	ASTM D4442	6%-10%, Ave≤9%	Pass
E-Rating (Formaldehyde Emissions)	ASTM D6007	P2≤0.05ppm	Pass
Immersion-Peel Test	ASTM D4222	No Peeling	Pass
High-low Temperature Cycle	ASTM D1211-1997	Without clear blister or crack after 8 cycles or more	Pass
Modulus of Elasticity (MOE)	GB/T 17657-2013	≥4000 Mpa	Pass
Modulus of Rupture (MOR)	GB/T 17657-2013	≥30 Mpa	Pass
Gloss Value	As customer's requirement	5-10°	Pass
Hardness of Coating	ASTM D3363-2005	≥2H	Pass
Scratch Resistance	EN 438	≥2N	Pass
VOC	Floorscore	Floorscore Certified	Pass

**www.BIYORKCANADA.COM**

Biyork product specifications are subject to change.  
Please always refer to a physical sample for reference.  
All rights reserved 2020.