



Internal extractors

For extracting inner bearings, bearing outer rings and bushings.

21



- 21-0
- 21-00
- 21-01
- 21-02
- 21-1
- 21-2
- 21-3
- 21-4
- 21-5
- 21-6
- 21-7
- 21-8
- 21-9
- 21-89
- 21-90









Description

- Mechanical pressure screw.
- Milled thread treated with special coating.
- Strong design, high performance and long service life.
- Safety label to ensure protection of intellectual property.

Advantage

- The 2-shell design with extra large grasp edges ensures safe extraction.
- The internal extractors are equipped with an internal safety stop to protect against excess tension and overloading.
- Product video can be opened directly on the tool using the QR code.
- Kukko internal extractors can be combined with counter supports and slide hammers.
- When combined with the internal extractors, extensions from series 21-V enable deeper bearings to be extracted.

Art.-No.	 40211761	 mm	 mm	 mm	 Segment	
21-0	-010408	5 - 8	14	73	2	22-1, 22-0
21-00	-010576	6 - 10	14	73	2	22-1, 22-0
21-01	-010651	8 - 12	14	73	2	22-1, 22-0
21-02	-010736	10 - 14	14	73	2	22-1, 22-0
21-1	-010811	12 - 16	25	72	2	22-1, 22-0
21-2	-010996	14 - 19	27	72	2	22-1, 22-0
21-3	-011153	18 - 23	35	89	2	22-1, 22-2, 22-0-1, 22-0
21-4	-011238	20 - 30	40	92	2	22-1, 22-2, 22-0-1, 22-0
21-5	-011498	28 - 40	23	101	2	22-1, 22-2, 22-0-1, 22-0
21-6	-011566	35 - 46	50	113	2	22-2, 22-3, 22-0-1
21-7	-011641	45 - 58	85	135	2	22-2, 22-3, 22-0-1
21-8	-011726	56 - 70	85	133	2	22-2, 22-3, 22-0-1
21-9	-011986	70 - 100	95	166	2	22-3, 22-0-1
21-89	-011801	56 - 110	120	187	3	22-4, 22-0-2
21-90	-012068	100 - 200	175	220	3	22-5, 22-0-2

Needle bearing extractors

To extract internal needle bearings.

21-4x









Description

- Mechanical pressure screw.
- Milled thread treated with special coating.
- Strong design, high performance and long service life.
- Safety label to ensure protection of intellectual property.

Advantage

- The 2-shell design with extra large grasp edges ensures safe extraction.
- The internal extractors are equipped with an internal safety stop to protect against excess tension and overloading.
- Product video can be opened directly on the tool using the QR code.
- Kukko internal extractors can be combined with counter supports and slide hammers.
- When combined with the internal extractors, extensions from series 21-V enable deeper bearings to be extracted.

Art.-No.	 40211761	 mm	 mm	 mm	 Segment	
21-40	-411526	9,6 - 18	18	92	2	22-1, 22-2, 22-0-1, 22-0
21-41	-186066	11,5 - 19	18	92	2	22-1, 22-2, 22-0-1, 22-0
21-42	-186141	12,5 - 21	19	92	2	22-1, 22-2, 22-0-1, 22-0
21-43	-186226	14,5 - 22	19	92	2	22-1, 22-2, 22-0-1, 22-0
21-44	-186301	16,5 - 23	23	92	2	22-1, 22-2, 22-0-1, 22-0
21-45	-186486	18,5 - 24	23	92	2	22-1, 22-2, 22-0-1, 22-0
21-46	-186554	20 - 25	23,5	92	2	22-1, 22-2, 22-0-1, 22-0