

TRUE GRIT™ 30

ROOFING UNDERLAYMENT

Proudly made in North America



Florida Building Code Approved FL22409
Meets ASTM D226 Type II and ASTM D4869

TRUE GRIT™ 30 is our 30# 6 mil synthetic roofing underlayment that features **TRUE GRIT Technology™**, a top-side coating that provides an incredibly coarse, sandpaper like grip. It provides superior traction underfoot and allows you and your team to focus on installing, while **TRUE GRIT Technology™** focuses on your safety.

Benefits

- **TRUE GRIT Technology™**
- No tears - Much stronger than 30# asphalt felt
- Light - Easier to handle and carry than felt
 - 10 Sq. TRUE GRIT 30 weighs 22 lb
 - 2 Sq. 30# asphalt felt weighs 42 lb
- **90 Day UV exposure**
- No asphalt - will not rot, dry-out, nor support mold growth
- No buckling, warping or cracking
- Dependable long term moisture protection for the roof
- Lays flat for quick and easy install
- Less laps - 48" wide TRUE GRIT 30 vs. 36" asphalt felt
- Cool blue color to reduce heat absorption on install
- **25 Year limited warranty**
- 100% Recyclable - Considered a green building product

Specifications

ROLL SIZE	10 SQUARES	4 SQUARES
Surface Covered	1000 ft ² (92.9 m ²)	400 ft ² (37.2 m ²)
Length	250 ft (76.2 m)	100 ft (30.5 m)
Width	48" (1219 mm)	48" (1219 mm)
Rolls per Pallet	56	120
Weight per Roll	22 lbs	9 lbs

PROPERTIES	TEST METHOD	TRUE GRIT™ 30
Breaking Strength (lbf/in-width)	ASTM D 226	64 Longitudinal (with fiber grain)
	ASTM D 226	66 Transverse (across fiber grain)
Tear Resistance; min; (lbf)	ASTM D 4073	77 MD Longitudinal (with fiber grain)
	ASTM D 4073	76 CMD Transverse (across fiber grain)
Pliability	ASTM D 228	Pass - Longitudinal / Transverse
Behavior (loss) on Heating	ASTM D 228	- 0.0
Liquid Water Transmission [Pass/Fail]	ASTM D 4869	Pass
Dimensional Stability (%)	ASTM D 1204	2.5 Longitudinal (with fiber grain)
	ASTM D 1204	2.5 Transverse (across fiber grain)
Unrolling @ 30°F and 140°F; [Pass/Fail]	N/A	Pass
Nominal Thickness	ASTM D1777	6 mils



Atlantic Coated Papers 1605 McEwen Dr. Whitby, Ontario L1N 7L4 1-886-299-1675

atlanticcoatedpapers.com