







INSTALLATION GUIDELINES

- I) EXHAUST IS AIMED AWAY FROM OR PARALLEL TO THE STRUCTURE.
- 2) EXHAUST IS NOT DIRECTED AT PLAY AREAS, PATIOS OR OTHER AREAS WHERE PEOPLE CONGREGATE.
- 3) THE NEAREST WINDOW, VENT, DOOR OR SIMILAR STRUCTURE OPENING IS AT LEAST 5 FEET FROM THE EXHAUST END OF THE GENERATOR.
- 4) GENERATOR SET MUST BE INSTALLED A MINIMUM OF 18 INCHES FROM STRUCTURE PER NFPA 37, HOWEVER, ACTUAL DISTANCE MAY DIFFER BASED ON STATE AND LOCAL CODES.
- 5) WINDOWS & DOORS ON ADJACENT WALLS ARE CLOSED.
- 6) FURNACE AND OTHER SIMILAR INTAKES ARE AT LEAST 10 FEET FROM EXHAUST END OF GENERATOR.
- 7) 4" THICK CONCRETE PAD EXTENDING 6" BEYOND GENSET ON ALL SIDES.



D

В

- 8) NO PLANTS, SHRUBS OR OTHER COMBUSTIBLES ALLOWED IN CLEARANCE AREA. (MINIMUM 8 FT. FROM EXHAUST END).
- 9) SENSITIVE PLANTS, PATIO FURNITURE, ETC. ARE AT LEAST 8 FEET FROM EXHAUST END OF SET.
- 10) REFER TO OWNERS MANUAL FOR OTHER INSTALLATION CONSTRAINTS.

						UNLESS OTHERW ALL DIMENSI GENERAL TOL X.XX ± 0.2	ONS IN ERANCES 5	MILLIMETERS :
	REV	DATE	CHANGE NUMBER	ON COMPOSITE DWGS, SEE PART NO. FOR REVISION LEVEL I INDICATES PART NUMBERS AFFECTED BY LATEST DRAWING REVISION	BY	X.X ± 1.0 X ± 1.5 ANGLES ± 0'	30 ′ SU	MAX.
						THIRD AND	ELE PRO	JECTION
ŀ	-	22JAN2021	CT209473	NEW DRAWING	RVM		$) \subseteq$	
ŀ						MAJOR	0=	0
ŀ						CRITICA	L 🖎 =	0
ŀ						CHARACTERIST KP	S-8002	OMPLY WITH 2
						DRAWN RV BY	′M	DATE:
Α						APPROVED T	4 S .	22JAN20

DO NOT SCALE.
THIS ASSEMBLY OR PART MUST
COMPLY WITH PEP-RML-001.
REFERENCE CAD MODEL FOR
UNSPECIFIED DIMENSIONS.



SCALE: 0.150 SHEET SIZE: B SHEET 2 OF 2

DIMENSION PRINT, 24RCLA
DWG NO.: ADV-9758

THIS DRAWING IN DESIGN AND DETAIL IS KOHLER CO. PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH KOHLER CO. WORK, ALL RIGHTS OF DESIGN OR INVENTION ARE RESERVED.