

## RC105c4



### Specifications:

Channels	no	4
Class	Type	AB
Power @14,4V /1.0% THD		
@ 4 ohm stereo:	Wrms	4x 105
@ 2 ohm stereo:	Wrms	4x 150
@ 4 ohm mono:	Wrms	2x 300
Operation supply	V	<b>10 -16</b>
Thermal protection	°C	80
THD @ 4 Ω / 50% Pmax	%	0.25
Signal/noise (1V)	dB	99
Band width +- 1 dB	Hz	20-20000
Input sensitivity	Vrms	0.2-10
Low input impedance	Ω	5k
High input impedance	Ω	50( with RC-HLT)
Damping @ 1000 Hz		65
Power consumption, idle	A	0.96
Power cons. 4 Ω stereo	A	45
Weight	kg	3,3
Dimensions (over all)	l/w/h	357/150/52mm
Dimensions (Heatsink)	l/w/h	318/150/52mm

### Features:

- Input with low- or high-level signal
- Stable at 2ohm stereo per channel and 4ohm bridge mode
- High-level with autosense function (no remote signal required)
- Variable switchable Low Pass Filter from 45 to 225 Hz or
- Variable switchable High Pass Filter from 45 to 225 Hz
- Optional Level control for CH3/4 (sRTC)

### Miscellaneous:

- Protection for overheating, overloading, short circuitry and speaker DC protection
- Massive heavy aluminum-heat sink