

AquaMetix®

Candle—Gravity Block



AquaMetix® Gravity Block



The AMX gravity block is designed to provide high quality drinking water for pour through and gravity type applications for municipally treated water supplies. This molded block technology is specifically designed to reduce particulate and chemical compounds including, chloramine, chlorine, lead, heavy metals, fluoride, Volatile Organic Compounds, Trihalomethanes (THM's), mercury, chromium, and more. This filter is designed specifically for gravity and low pressure applications and requires no priming or pre-wetting procedures.

This filter will reduce a wide variety of drinking water contaminants of both aesthetic and health concern. The dense pore structure and vast surface area is ideally suited for reducing chemical compounds.

- Working pressureNONE- Gravity Feed
- Maximum working temperature 100° F
- Minimum working temperature 40° F
- Unrestricted flow > 1 gallon per hour with 2 inches of head pressure
- Recommended change frequencyevery 12 months

Performance Data

- >95% reduction—Chloramines
- >95% reduction—Chlorine
- >95% reduction—Chromium
- >98% reduction—Lead & Mercury
- >95% reduction—Heavy Metals
- >97% reduction—Fluoride
- >99% reduction—Glyphosate (pesticide)
- >95% reduction—Pharmaceutical compounds
- >95% reduction—VOC's (Volatile Organic Compounds)
- >95% reduction—THM's (Trihalomethanes)

Capacity

1150 Gallons—Chloramines
750 Gallons—Lead

Size

2" x 6" Slimline with supplied wingnut and washer for gravity feed

Application

AquaCera® Gravity Systems

** filters will fit most competitor type gravity feed systems*

Part Number

AMX-6GB

Tested to meet or exceed ANSI/NSF Standards 42 & 53 for specified claims reduction

Manufactured in the USA

