

Excursion™

Mini Gravity Filter

Personal Gravity Filter Instruction Sheet



ASSEMBLY INSTRUCTIONS:

1. Remove the housing and filter from their protective packaging, checking each item against the diagram.
2. Extreme cleanliness is important. Sterilize all parts, except the filter element, before assembly.
3. Place the sealing washer (5) over the threaded part of the filter element (4).
4. Place the element (4) into the hole in the base of the upper section (1).
5. Screw the wing nut (6) onto the threaded part of the filter element extending through the base of the upper section. Hand-tighten the wing nut to seal and compress the sealing washer to secure the filter element in place.
6. Place the upper section (1) onto the bottom section (2) and place the lid (3) on top of the unit. Assembly is now complete.

OPERATION:

1. Remove lid (3) and fill upper section (1) with water.
2. Filtered water will collect in the bottom section (2) ready for use.

Note: The first supply of filtered water should be discarded as it may contain loose material washed from the filter element.

SERVICING:

The ceramic filter element (4) should be cleaned when there is a noticeable drop in filtration time.

To clean the elements:

1. Remove the element (4) from the upper section (1) by unscrewing the wing nut.
2. While holding the element under running water or in a bowl of water, scrub the element with a brush or 3M Scotchbrite pad. Always scrub away from the threaded end of the element.

Note: NEVER use soap or detergents to clean the filter element.

3. Reassemble the element as detailed above.

Note: Filter element should be replaced annually.

Note: Regular cleaning of the housing is recommended, use mild soap and a non-abrasive material to clean the stainless steel.

Note: This gravity filter is designed to remove harmful bacteria and harmful chemicals from water; it will not remove dissolved solids.

