

TEE 1st FULL INVERTE DEHUMIDIFIER

FULL-INVERTER DEHUMIDIFIER SPECS (R32)

| Model | IDHR60 | IDHR96 | IDHR120 |
|-----------------------------------------|----------------|--------------|--------------|
| Advised pool surface (m ²)* | ≤25 | ≤40 | ≤50 |
| Operating air temperature (°C) | 10~38 | | |
| Capacity (l/h) (Air 30°C, RH 80%)* | 2.5 | 4.0 | 5.0 |
| DER (l/h.kW) (Air 30°C, RH 80%)* | 4.00~3.40 | 4.53~4.05 | 4.50~3.68 |
| Heat recovered (kW) | 2.4 | 3.3 | 4.4 |
| Electric heating optional (kW) | 1.3 | 2.1 | 2.1 |
| Rated power (kW) | 0.11~0.73 | 0.17~0.99 | 0.22~1.36 |
| Rated current (A) | 0.48~3.17 | 0.74~4.30 | 0.96~5.91 |
| Power supply | 230V/1 Ph/50Hz | | |
| Sound pressure at 1 m dB(A) | 38.3~45.6 | 40.3~45.8 | 39.9~46.4 |
| Air flow (m ³ /h) | 600 | 800 | 1000 |
| Net dimension LxWxH (mm) | 850x291x770 | 1120x291x770 | 1220x291x770 |
| Net weight (Kg) | 53 | 68 | 72 |
| Qty per 20'FT / 40'HQ (sets) | 84/258 | 60/195 | 58/189 |

* Above data is subject to modification without notice.



www.fairland.com.cn
0086-20-87321933
E-mail: Sales@fairland.com.cn
Fairlandchina Fairlandchina

Fairland Electric (China) Limited
Room 2315-2317, No.69 Xianlie Road Central,
Guangzhou, P.R.China, 510095



1st

Full-inverter
Dehumidifier



50%

power consumption of traditional dehumidifier



10
times

quieter than traditional dehumidifier
quieter than a fridge

×10



- Metal & Aluminum alloy perfectly match



- Environment friendly refrigerant

