

Product data sheet Characteristics

MX9B357P

Clipsal MAX9 Pin Type Comb Busbar, 3P, 100 A, 57 Modules





Product brand	Clipsal
Range	MAX9
Product or component type	Comb busbar
Total number of 18 mm modules	19



Complementary

Number of ways	19 ways 3 L
Poles configuration	19 x 3P
Connection pitch	18 mm
Insulation	Insulated
Device presentation	Cuttable
Provided components	10 end-pieces Tooth covers
[le] rated operational current	100 A
[Ue] rated operational voltage	400 V AC
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Mounting mode	Horizontal
Mounting location	Тор
Height	35 mm
Width	1010 mm
Depth	10 mm
Colour	Grey

Environment

Standards	AS/NZS 61439-3 AS/NZS 3000	
Fire resistance	960 °C	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.5 cm	
Package 1 Width	3.3 cm	
Package 1 Length	101.0 cm	
Package 1 Weight	662.0 g	
Unit Type of Package 2	CAR	

Number of Units in Package 2	10	
Package 2 Height	9.5 cm	
Package 2 Width	10.5 cm	
Package 2 Length	103.0 cm	
Package 2 Weight	7.22 kg	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

***	_
Warranty	7-vear
vvarianty	r-year

Life Is On

2