



## TA85R/L TABLET ARM ASSEMBLY


**Parts included:**      **Tools needed:**

- 1 Tablet
- 1 Tablet arm
- 1 Clip
- 4 Brackets
- 8 Phillip head screws for brackets
- 1 Phillip head screw for clip

Phillips head screw driver



tablet



tablet arm

brackets

screws

clip

front brace

rear brace

screw for clip

**Assembly:**

1. Align tablet arm with pre-drilled holes on underside of tablet.
2. Place brackets on tablet arm and secure to tablet with screws. (Do not over-tighten.) For "flip top" tablet, do not install brackets in center of tablet. (Fig. 1)

**Installation of tablet arm onto 8500 series chair:** (Visit [www.nationalpublicseating.com](http://www.nationalpublicseating.com) for a video demonstration.)

1. Align rear brace of tablet arm with rear leg of chair as shown in picture. (Fig. 2, Fig. 3)
2. Position front brace of tablet arm over front leg of chair. (Fig. 2, Fig. 4)
3. Push firmly down on tablet arm to lock into position.
4. Secure narrow part of clip to the portion of the tablet arm that is parallel to seat frame, then secure wider portion of the clip to the seat frame. (Fig. 5)
5. Align slit in clip with hole in table arm, then secure clip to table arm with Phillip screw. (Fig. 6)
6. Make sure to push down table arm while securing wider portion of the clip to the seat frame. (Fig. 7)

**CAUTION:**  
Ensure that all screws are properly installed before using unit. Check all screws periodically. Failure to completely tighten the screws may result in tipping and possible injury.




Fig. 1



Fig. 2



Fig. 3



Fig. 4





Fig. 5



Fig. 6



Fig. 7



Dear Customer,  
Thank you for your purchase. Although great care goes into manufacturing and packaging of this product, mistakes are possible. If you encounter any missing parts or have difficulty with assembly, please contact our customer service Toll Free at 1-800-261-4112 for immediate and courteous service.