

BOIS

Bois is a wood-look porcelain tile with a lightly rippled surface, reminiscent of floors beautifully worn by centuries of use. It's an excellent choice for residential playrooms, basements, garages, and varied commercial spaces. Offered in both 10" x 60" "planks" and 4-5/16" x 21-1/4" chevrons in a warm palette of Avorio, Ecrú, Miele and Tobacco.



BOIS

Plank Format

Not to scale*



Avorio
Recommended Grout color: Sugar Cookie

Ecrú
Recommended Grout color: Vintage Linen

Miele
Recommended Grout color: Vintage Linen

Tabacco
Recommended Grout color: Vintage Linen

Chevron Format

Not to scale



Avorio
Recommended Grout color: Sugar Cookie

Ecrú
Recommended Grout color: Vintage Linen

Miele
Recommended Grout color: Vintage Linen

Tabacco
Recommended Grout color: Vintage Linen

APPLICATIONS									ATTRIBUTES		VARIATION	
INTERIOR FLOOR	INTERIOR WALL	SHOWER WALL	SHOWER FLOOR	EXTERIOR FLOOR	EXTERIOR WALL	POOL/ FOUNTAIN	COUNTER TOP	FIREPLACE SURROUND	DCOF ¹	0.50		
Light/ Medium Commercial ¹	All	Yes, including steam	Yes, in mosaic formats only ²	No	Yes, including freeze thaw	No	Yes ³	Yes				
INSTALLATION/MAINTENANCE										AVAILABLE SIZES		
SETTING MATERIAL	GROUT	GROUT JOINT	MEMBRANE	CAULK	SEALER	CLEANER	INSTALLATION INSTRUCTIONS	LAYOUT	DRY LAYOUT	<p>PORCELAIN RECTIFIED FIELD TILE 10⁷/₁₆" × 62¹⁵/₁₆" × 3³/₈" Matte</p> <p>PORCELAIN FIELD TILE 4⁵/₆" × 21¹/₄" × 3³/₈" Matte</p>		
Ardex XS White Medium Bed Mortar ⁴	Ardex FL Rapid Set Sanded ⁵	1/16" minimum	Ardex B+9	Ardex SX	AquaMix Sealers Choice Gold	AquaMix Concentrated Cleaner	TCNA Handbook	Max. 25% Offset	Recommended			
NOTES												
¹ Residential Heavy for Chevron plank formats ² No Shower floor application for Chevron plank formats ³ No Counter top application for Chevron plank formats ⁴ Alternate Setting Material - Mapei Ultraflex LFT White ⁵ Alternate grout - Mapei Ultracolor Plus FA or Mapei Flexcolor CQ Tech Note: Running Bond/Brick Joint Patterns To Be Set With A Max. Offset Of 25% And Min. Grout Joint Of 1/16", Unless Otherwise Approved By Owner. Number Of Faces 48, 4.564 SF/PC. DCOF AcuTest Wet ≥ 0,50.												