





FIOR DI PESCO

A classical marble with muted, tonal palette of soft grey with tints of rose and teal, strongly accented by stunning veins in pearl white, blush, raisin, and the rich peach that give this stone its name.
Stocked in 2cm polished slabs, quarried in Italy.



2cm
Polished

APPLICATIONS										INSTALLATION/ MAINTENANCE		TAILORED TO CUSTOMIZATION	
ACID SENSITIVITY	COUNTER TOP	INTERIOR FLOOR	INTERIOR WALL	SHOWER WALL	SHOWER FLOOR	EXTERIOR FLOOR	EXTERIOR WALL	POOL/ FOUNTAIN	FIREPLACE SURROUND	SETTING MATERIAL	INSTALLATION INSTRUCTIONS	CARPET CUTTING	FIELD
High ¹	Yes	Light / Med Traffic Commercial ⁵	All ⁵	Conventional Only ²	No	No	No	No	Yes	Mapei Kerapoxy 410 ³	MIA DSDM ⁴	MOSAIC	SADDLE
												VANITY TOP	WATERJET

ORIGIN	VARIATION	SLAB	MATERIAL
 <p>Quarried in Italy</p>		 <p>3/4 (2CM) POLISHED</p>	 <p>MARBLE</p>

NOTES

- ¹ This material is highly sensitive to acids. When used as a kitchen countertop, acid etching will be highly visible. Do not use this material if acid etching is a concern. For kitchen countertops we recommend a honed finish. Expect material to patina over time and create a beautiful rustic/antique look.
- ² Regarding Fiberglass Mesh Backed Stones for installation in wet areas, consult your fabricator for recommended installation method. Options include, but are not limited to complete removal of fiberglass mesh backing (where applicable) or installing with epoxy setting material. Any decision to install contrary to most current Marble Institute of America Dimension Stone Design Manual practices is solely at buyers discretion and risk.
- ³ May have fiberglass mesh backing, choose setting materials accordingly.
- ⁴ Please see MIA DSDM (Dimension Stone Design Manual) for all installation instructions.
- ⁵ Recommended Grout Spacing: Interior Floor - 1/8" minimum, Interior Wall - 1/4" minimum.
Mortar Note: The MIA recommends installing resin-backed stone with epoxy-based setting materials. Consult your setting materials manufacturer for specific recommendations.