

WHITE SAND

White Sand is a beautiful neutral beige marble with delicate tonal veining and a smooth background.
Stocked in a variety of honed and polished mosaics and field tile.



WHITE SAND




12" x 24" Field Tile
Polished & Honed



24" x 24" Field Tile
Polished



11 3/8" x 12 1/8" Hexagon Mosaic
Polished



Raked 12" x 24" Textured Field Tile



24" x 48" Field Tile
Honed Finish

APPLICATIONS									VARIATION				TAILORED TO CUSTOMIZATION ¹	
INTERIOR FLOOR	INTERIOR WALL	SHOWER WALL	SHOWER FLOOR	EXTERIOR FLOOR	EXTERIOR WALL	POOL/ FOUNTAIN	COUNTER TOP	FIREPLACE SURROUND	V1	V2	V3	V4	CARPET CUTTING	FIELD
Light/Medium Traffic Commercial	All	Yes, Including Steam	Yes, in Mosaics Format Only	No	Yes, including freeze thaw	No	Yes	Yes					FINISH	MOSAIC
													SADDLE	VANITY TOP
													WATERJET	

INSTALLATION/MAINTENANCE									
SETTING MATERIAL	GROUT	GROUT JOINT	MEMBRANE	CAULK	SEALER	CLEANER	INSTALLATION INSTRUCTIONS	LAYOUT	DRY LAYOUT
Mapei Ultraflex LFT ²	Ardex FG-C Microtec Unsanded ³	1/16" minimum	Ardex 8+9 ⁴	Ardex SX ⁵	AquaMix Sealer's Choice Gold	AquaMix Concentrated Stone & Tile Cleaner ⁶	TCNA Handbook	No	Sample ⁷

AVAILABLE SIZES	
 3cm Hexagon 11 3/8" x 12 1/8" x 3/8" Polished	
	 Raked Textured Field Tile 12" x 24" x 1/2" Mixed Finish

NOTES
¹ 24"x48" Field Tile - No ² Alternate mortar - Grainrapid 2 - Part System or Ardex X77 Microtec Fiber Reinforced Mortar 24"x48" Field Tile mortar - Mapei Kerapoxy 410 ³ Alternate grout - Mapei Ultracolor Plus or Mapei Keracolor CQ 24"x48" Field Tile grout - Mapei Ultracolor Plus FA or Mapei Flexcolor CQ 24"x48" Field Tile membrane - Mapei Mapelastic AquaDefense 24"x48" Field Tile caulk - Mapei Keracaulk Sanded 24"x48" Field Tile cleaner - AquaMix Concentrated Cleaner ⁷ Layout for overview of material before installation. Tech Note: We strongly suggest a dry layout and 25% overage of material to allow for proper blending. Product must be installed in accordance with current TCNA Handbook Stone Methods. We strongly suggest a dry layout and 25% coverage of material to allow for proper blending. The Natural Stone Institute recommends installing resin-backed stone with epoxy-based setting materials. Consult your setting materials manufacturer for specific products.