WHITE SAND SLAB

White Sand is a beautiful beige Turkish marble with delicate tonal veining and a smooth background. This 3/4" (2cm nominal) slab is stocked in both polished and honed.




APPLICATIONS											LATION/ ENANCE	TAILORED TO CUSTOMIZATION
ACID SENSITIVITY	COUNTER TOP	INTERIOR FLOOR	INTERIOR WALL	SHOWER WALL	SHOWER FLOOR	EXTERIOR FLOOR	EXTERIOR WALL	POOL/ FOUNTAIN	FIREPLACE SURROUND	SETTING MATERIAL	INSTALLATION INSTRUCTIONS	CARPET CUTTING
												FIELD
												MOSAIC
High ¹	Yes	Light/Medium Commercial	All	Yes, including steam²	Yes, including steam²	No	Yes	No	Yes	Ardex WA Epoxy ³	NSI DSDM ⁴	SADDLE
												VANITY TOP
												WATERJET

ORIGIN

C

Quarried in Turkey







QR CODE LINK

NOTES

- 1 This material is sensitive to acids including those commonly found in kitchens. Acid etching occurs in many stones, but may be less visible on lighter colors and on surfaces with a honed finish. A professionally applied surface treatment like MORE™ AntiEtch™ can prevent acid etching.
- $^2\,Showers: Product\,MUST\,be\,installed\,in\,accordance\,with\,current\,TCNA\,Handbook\,Stone\,Methods.$
- ³ Setting Material: Ardex WA Epoxy, Mapei Kerapoxy 410 and Ardex P4 Primer + Ardex X77 White Microtec Fiber Reinforced Mortar
- $^{\rm 4}$ Please see NSI DSDM (Dimension Stone Design Manual) for all installation instructions.

 $Tech \, Notes: The \, NSI \, recommends \, installing \, resin-backed \, stone \, with \, epoxy-based \, setting \, materials. \, Consult \, your \, setting \, materials \, manufacturer \, for \, specific \, recommendations. \, Epoxy \, fill \, on \, face \, of \, slab \, to \, be \, expected. \, High \, veining \, and \, tone \, variation, \, expect \, color \, spots \, on \, some \, pieces.$