Specifications







JLC Series Lubricated Compressors				
Model Number		JLC 12	JLC 22	JLC 32
Total HP		1.0	2.0	3.0
User Capacity		1-3	3-5	5-7
Voltage		208-230	208-230	208-230
Line Frequency		60 Hz	60 Hz	60 Hz
Total Amps		6.0	12.0	18.0
Circuit Breaker (Amp)		20	20	30
CFM @ 80 PSI		5.3	10.6	15.9
No. of Heads		1	2	3
dB A		68	71	75
Tank Capacity		12 Gallons	20 Gallons	30 Gallons
Size (H x W x D)		28" x 28" x 22"	30" x 34" x 24"	33" x 39" x 25"
Temperature Range		40°F - 104°F	40°F - 104°F	40°F - 104°F
Shipping Weight (lbs)		220 lbs.	360 lbs.	520 lbs.

JDS offers nothing less than top of the line equipment. Every component and all features are tested for performance, bringing you the best quality. But quality is not even half of it. We strive for perfection and satisfactory service, keeping our customers on top of our list.

Finally, JDS proudly presents the JLC Series Lubricated Compressor. Designed by the very best, the JLC Series will leave you satisfied with everything you expect from your clean air source.

Key features

- Copeland TM powered heads provide the most quiet, reliable service.
- The 0.01 micron filter catches the smallest contaminants, leaving only the cleanest air possible. Dust? Oil? Smoke? Even bacteria can't pass through.
- Our exhaust silencer keeps the noise level to a minimum, and filters the purge air to keep your mechanical room clean.
- The purge tank/desiccant dryer system provides the cleanest and the most dry air possible, leaving you worry-free throughout the day.



JDS Dental Products | 21133 Norwalk Blvd. Hawaiian Gardens, CA 90716 Tel: 562 - 924 - 4300 | Fax: 562 - 924 - 2273 | Support@JDSmfg.com | www.JDSmfg.com