



## Leak Protection System

### General & Technical Information:

The Pure Water Systems Leak Protection System is your best defence against water damage.

This compact unit is designed to detect moisture using metal contacts on the Control Box which sound an alarm and shut off the water supply to the water filtration system. The Leak Detector gives you peace of mind that your home and your water filtration system are protected from potential water damage. This unit also has an inbuilt Cartridge Indicator that indicates when the filter cartridge is due to be changed.

### How Does It Work?

When detected by the metal contacts, the alarm is triggered which activates the Solenoid Valve to shut off the water supply to the water filtration system.

The Leak Warning Indicator will continuously blink blue. The alarm will continue to sound until the Leak Protection System is reset manually.

After resolving the leak, press and hold the Check/Reset button, the Leak Protection System will beep and reset the Solenoid Valve to return the water supply to the water filtration system.



### Features & Benefits

#### Ultra-Sensitive Sensor

Warns against the first sign of leaking

#### Quality Manufacture

Created by specialists in water control

#### Filter Life Monitor

Indicates when to change cartridge

### Warranty Information

Pure Water Systems offers a 3 year parts and labour warranty coupled with our Pure Quality Guarantee\*, ensuring that you are receiving the best quality water available and value for money to give you greater peace of mind.

—○ **CONTACT US**






**1300 808 966**

[www.purewatersystems.com.au](http://www.purewatersystems.com.au)

Refer to Pure Water Systems website for our Pure Quality Customer Satisfaction Guarantee

## SINGLE UNDERSINK SPECIFICATIONS

SPECIFICATIONS	
Operating Voltage	9V DC
Supply Current	Typical 1.0 mA, Maximum 15.0 mA
Cable Length	1.5m for Solenoid Valve Cord
Connecting	1/2" BSP Male
Working Temperature	0–60°C
Maximum Pressure	112 psi
Body Material	Chrome Plated Brass
Solenoid Valve	Chrome Plated Brass

SUPPLIED WITH			
	1 x Control Box		1 x 1/2" Swivel Connector
	1 x 9V Alkaline Battery		1 x Power Cord
	Installation Instructions		

CONTACT US

1300 808 966

[www.purewatersystems.com.au](http://www.purewatersystems.com.au)

Refer to Pure Water Systems website for our Pure Quality Customer Satisfaction Guarantee