



Safety Data Sheet 2020

Manufacturer / Distributor Information: 5 Star Finishes Ltd 200 4170 Still Creek Drive, Burnaby BC, Canada Telephone: (778) 682 4287 Prepared April, 2020 by 5 Star Finishes Ltd www.5starfinishes.ca

Product Identifier

SECTION 1. IDENTIFICATION

| | |
|--------------------------------------|--|
| Product Identifier | Canadian Clay |
| Other Means of Identification | American Clay, Venetian Plaster, Kaolin plaster, Strawbale plaster |
| Recommended Use | Interior wall finish |
| Restrictions on Use | Do not use on floors, swimming pools, shower stall, horizontal surfaces, backsplashes, water prone areas |
| Initial Supplier Identifier | 5 Star Finishes Ltd |
| Emergency Telephone Number | 778 682 4287 |

SECTION 2. HAZARD IDENTIFICATION

| | |
|-----------------------|--|
| Classification | Not Hazardous: Carcinogenicity-Category 1A Specific target organ toxicity, repeated exposure- Category 1 |
| Label Elements | |



| | |
|--------------------------|--|
| Signal Word | Danger |
| Hazard Statements | May cause cancer May cause damage to organs through prolonged or repeated exposure |
| Other Hazards | None known |
| Prevention | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Do not breathe vapor. |
| Response | Get medical attention if you feel unwell. If exposed or concerned: Get medical attention. |
| Storage/Disposal | Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations. |

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No. | Concentration |
|-------------------|-----------|---------------|
| Kaolin Grolleg | 1332-58-7 | 15-30 |
| Calcium Carbonate | 1317-65-3 | 30-70 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

SECTION 4. FIRST-AID MEASURES

Most Important Symptoms and Effects, Acute and Delayed

| | |
|--|---|
| Inhalation | May cause cancer through inhalation. Inhalation may increase the progression of tuberculosis; susceptibility is apparently not increased. Persons with impaired respiratory function may be more susceptible to the effects of this substance. Smoking can increase the risk of lung injury. Persons with pre-existing skin problems or impaired respiratory function may be more susceptible to the effects of this substance. Chronic exposure can cause silicosis, a form of lung scarring that can cause shortness of breath, reduced lung function, and in severe cases, death. |
| Skin Contact | No none effects |
| Eye Contact | Flush eyes if plaster gets in your eyes. Do not rub your eyes. |
| Ingestion | Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Immediate Medical Attention and Special Treatment | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. : No specific treatment. : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. See toxicological information (Section 11) |

Eye Contact: Immediately flush eyes with gentle but large stream of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Call a physician immediately. Inhalation: Move to fresh air. If not breathing, administer artificial respiration. If breathing is difficult, give oxygen. Always wear a respirator when mixing dry mixes or sanding plaster. SEEK MEDICAL ATTENTION. Ingestion: DO NOT INDUCE

VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Call a physician immediately. Chronic Exposure: Seek medical professional Aggravation of Pre-existing Conditions: Seek medical professional

SECTION 5. FIRE-FIGHTING MEASURES

| | |
|---|---|
| Extinguishing Media Suitable | Use an extinguishing agent suitable for the surrounding fire. |
| Extinguishing Media Unsuitable | None known |
| Extinguishing Media Specific Hazards Arising from the Product | Thermal oxidative decomposition can produce calcium oxide. |
| Special Protective Equipment and Precautions for Fire-Fighters | None known |
| Fire rating | 0 Non combustible solid |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| Personal Precautions, | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| Protective Equipment, Emergency Procedures | None known |
| Method for Containment and Cleaning UP | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. Wear dust mask or suitable respirator when cleaning dry goods. |

SECTION 7. HANDLING AND STORAGE

| | |
|--------------------------------------|---|
| Precautions for Safe Handling | Some products are in 20 kg 5 gallon containers or 20 kg bags. Use appropriate care in lifting / handling heavy materials. |
| Conditions for Safe Storage | Keep bags and containers at room temperature and not in direct sunlight. Keep bags and buckets tightly closed, and ensure they are not able to spill over. Do not over stack buckets or bags on top of each other, creating a danger of breakage or falling over. |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

| Chemical Name | ACGIH® TLV® | OSHA PEL |
|---------------------|----------------------|---|
| Kaolin | | 2mg/ m ³ |
| Silica, crystalline | | ((30 mg/m ³)/(%SiO ₂ +2) TWA (total)) |
| Inorganic Dust | | 4mg/ m ³ |
| Calcium carbonate | 10 mg/m ³ | 15 mg/m ³ (total); 5 mg/m ³ (resp) |
| | | |

Appropriate Engineering Controls Individual Protection Measures Eye/Face Protection

None known

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Eye/face protection Skin protection Hand protection Body protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields

Skin Protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odour Odour Threshold pH Melting Point and Freezing Point Initial Boiling Point and Boiling Range Flash Point Evaporation Rate Flammability (solid, gas)

White/Cream colored powder
Almost odourless
No information found
4
No information found
No information found
No information found
No information found
No information found
Fire rating 0 (non combustible)

| | |
|---|----------------------|
| Upper and Lower Flammability or Explosive Limit | No information found |
| Vapour Pressure | 0 mm Hg |
| Vapour Density (air = 1) | No information found |
| Relative Density (water = 1) | No information found |
| Solubility in Water | Not Soluble |
| Solubility in Other Liquids | No information found |
| Partition Coefficient, n-Octanol / Water (Log Kow) | No information found |
| Auto-ignition Temperature | None |
| Decomposition Temperature | n/a |
| Viscosity | 1800-2400mpa |

SECTION 10. STABILITY AND REACTIVITY

| | |
|---|--|
| Reactivity | No specific test data related to reactivity available for this product or its ingredients. : |
| Chemical Stability | Stable |
| Possibility of Hazardous Reactions | Under normal conditions of storage and use, hazardous reactions will not occur. Air, dusting, and incompatibles. |
| Conditions to Avoid Incompatible Materials | No information found |
| Hazardous Decomposition Products | None known |
| Hazardous Decomposition Products | Decomposition of product could result in Calcium Oxide |

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

4 Inhalation 1 Skin contact 2 Eye contact 1 Ingestion (1- low 5-high)

Acute Toxicity

LC50

LD50 (oral)

LC 50, 96 Hrs, Fish mg/l >1000 EC 50, 48 Hrs, Daphnia, mg/l >1000 IC 50, 72 Hrs, Algae, mg/l >1000

LD50 (dermal)

No information found

Notes

Skin Corrosion / Irritation

N/A

Serious Eye Damage / Irritation

Causes minor eye discomfort

STOT (Specific Target Organ Toxicity) - Single Exposure

May cause respiratory irritation.

Aspiration Hazard

STOT (Specific Target

Causes damage to organs through prolonged or repeated exposure.

**Organ Toxicity) -
Repeated Exposure
Respiratory and/or
Skin Sensitization**

Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.

Carcinogenicity May cause cancer (**silica**)

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity None
Persistence and Degradability Information not found
Bioaccumulative Potential This material shows no bioaccumulation or food chain toxicity potential.
Mobility in Soil Information not found
Other Adverse Effects Information not found

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods This material must be disposed of in accordance with all local, provincial, and federal regulations. Recycle all paper bags, plastic pales and lids in appropriate recycling facilities.

SECTION 14. TRANSPORT INFORMATION

Freight Class: 50 (dry goods), 55 (wet / mixed goods) Handling unit: Plaster, calcined; stucco, calcined, patching compound HS Code (Harmonized Tariff): 2520.20.00

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations The components of this mixture are listed or are exempt from listing in the Toxic Substance Control Act Inventory of Chemical Substances. This product does not contain any chemicals that would require export notification. This product contains no: Cadmium (Cd), Chromium (Cr), Lead (Pb), Tin (Sn), nor any organic elements that can cause cancer. This product contains no ozone-depleting compounds.

SECTION 16. OTHER INFORMATION

Date of Latest Revision Nov 24/2020

Further information Crystalline silica: Raw materials in this product may contain respirable crystalline silica.

Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

5 Star Finishes Ltd provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. 5 Star Finishes Ltd **MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, 5 Star Finishes Ltd WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.**
