

ANTENNA MOUNTING BRACKET

TLR742401











PRE-INSTALLATION



Read through this installation guide before proceeding.



Fitting time is approx. 40 minutes.



Basic spanner and socket set, Allen Keys, Torx set

FITTING KIT	
QUANTITY	PART
1	TLR742401-1 mounting bracket
2	TLR742401-2 packer
2	M8 x 30mm S/S button head
3	Cable tie 150mm

NOTE: This TLR Products bracket allows for mounting of UHF Antenna to the rear door hinge of a Suzuki Jimny







PHOTO 2



РНОТО 3

FITTING INSTRUCTIONS

- 1. Remove hinge cover panel, the plastic cover is only held on my 2 small push clips and can be removed by levering the cover panel off.
 - NOTE: be careful not to damage paint, we recommend using something made from plastic or similar.
- 2. Ensure door is latched shut and remove 2 hinge mounting bolts as shown in photo 1.
- 3. Assemble TLR Products components, see photo 2, and mount into place using hardware supplied –photo 3.

 NOTE: take care to make sure you align the bracket upright, you may need to adjust angle once antenna is mounted in place.
- 4. Fit Antenna into bracket and route cable around below hinge, use cable ties to fix cable into position and ensure the cable will not be pinched in operation of the rear door.
- 5. Run cable down and connect to UHF unit as per suppliers' recommendation.



