



WIRING INSTALLATION

- 1) Take connectors shown in Figure 1 and Plug them into the factory harness ensuring they clip in securely.
- 2) Plug the other end with the Deutsch connector plug into your Optimus Round lights.

Figure 1



WARNINGS

As with many other high-tech products, this VISION X Jeep JK LED Fog Light Kit requires a bit of attention before you can use it. Please read the accompanying information carefully first.

- 1) Don't stare directly into the light or shine directly into the eyes of another person as this may cause temporary loss of vision.
- 2) Never disassemble the products, as all parts must be factory serviced to insure proper operation and will void warranty if opened.
- 3) The LED light is to be mounted on the vehicle only in a vertical, bottom-mounting, or in a suspended position.
- 4) After turning on the light, the housing may be hot enough to warrant a burn risk. Be careful when you touch the body after turning on the light for a long period of time.
- 5) Use the supplied wire adapters for electrical installation.
- 6) Ensure the LED light does not adversely affect the performance of low beam, high beam, engine cooling or the driver's view.

JEEP JK LED FOG LIGHT KIT

Installation Instructions & User's Manual



www.VISIONXUSA.com

VISION X JEEP JK KIT



Installation Instructions & User's Manual



1	Optimus Round & Brackets
	
LED Light & Bracket	Qty: 2

2	Plug & Play Connector
	
Part (M1)	Qty: 2

APPLICATION GUIDE

- At this time this kit has been tested to fit 07-12 Jeep JK with factory fog light provisions.
 - 07-09 Jeep JK – 9005 Connector
 - 10-12 Jeep JK – H16 Connector

MAINTENANCE

- All VISON X models have been designed for maintenance free use. In the case a LED lamp or other part replacement please contact your authorized service center.

MOUNTING INSTALLATION

- Start off by removing your factory fog lights along with their housings. Save the mounting hardware as it will be used later in the install.
- Insert the lights into the factory fog location. Make sure the lights can move as you will need this movement to get the lights to line up flush in the housings.
- Using the three holes in each side of the bracket as shown below loosely mount the lights with the brackets attached using the original hardware.
- With the assembly in the fog light mounting opening, tighten all bolts securely to prevent future movement.

WARNING: Bolts, Nuts, & Washers are Stainless Steel.

Do Not Use Pneumatic or Power Tools to Tighten & Loosen Mounting or the Threads Can Seize

