



NC305XC Security Camera

Tons of features packed into one well priced camera. PIR. Excellent proactive deterrent. White light to illuminate or strobe. Speak to talk through the mobile app or set off the siren. Now with Smart IR

5
MEGA
PIXELS

2.8mm
LENS

PIR

Specifications

Camera Type	Bullet
Image Sensor	1/2.7" Progressive CMOS
Maximum Video Resolution (Megapixels)	5
Maximum Video Resolution	2592 x 1944
Lens	2.8 mm (H.FOV: 92°)
Lens Type	Fixed
Maximum Night IR Distance (M)	20
Video Compression	H.265+, H.265, H.264+, H.264, MJPEG
ONVIF depends on firmware version	ONVIF(Profile S/G/T) 21.12 or greater, Http API
IP Rating	IP66
Operating Environment	-10°C to 55°C (14°F-131°F) Humidity: 20%-80% RH
Dimensions	70mm×155mm
Weight (Net)	0.44
Accessories	IV2422X, IV2477X
Power Supply	Power over Ethernet IEEE 802.3af, DC12V
Power Consumption	4.2 W
Connectors	RJ-45 , DC Power Input
Outdoor Use	Yes
IP Rating	IP66
Vandal Resistant	Yes
Frame Rate at Resolution	20
Day/Night Mode	Auto
Image Enhancement	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction
Edge Recording microSD/SDHC Card	Micro SD/SDHC Card
Multiple Streams (encode format)	3 Streams
Audio Streaming	Yes (microphone and speaker included)
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPoE, UPNP, SMTP, SNMP, P2P (QR code)
Intelligent Video (IVS)	Motion Detection, PIR
Cloud option (camera only)	Dropbox
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
Power Over Ethernet	Yes"
Ethernet	Ethernet (10/100 Base-T)
In The Box	Free Software available from FAQ, Printed quick user guide, installation template, mounting screws and plugs
Warranty	3 Year Warranty