



NC528XB Security Camera

Sony Sensor and long-range 80m IR. Excellent perimeter detection. IVS for human and vehicle detection.









Specifications

O	D. II .
Camera Type	Bullet
Image Sensor	1/2.7" Progressive CMOS
Maximum Video Resolution (Megapixels)	5
Maximum Video Resolution	2592 x 1944
Lens	5-50 mm (H.FOV: 50.9 to 7.6°)
Lens Type	Motorised Zoom
Maximum Night IR Distance (M)	80
Image clarity	3.5
Connectors	RJ-45 , Analog Video Out, Audio In, Audio Out, Alarm in or out *4
Video Compression	H.265, H.264
ONVIF (depends on firmware version)	2.6
Operating Environment	-30 to +55°C/less than ≤ 95% RH
Dimensions	Ø108 X 301mm
Weight (Net)	1.468
Accessories	IV2422X
Power Supply	Power over Ethernet IEEE 802.3af, DC12V
Power Consumption	<10W
Connectors (web)	RJ-45 , DC Power Input, Analog Video Output, Audio In, Audio Out, Alarm in or out *4, reset button
Outdoor Use	Yes
IP Rating	IP66
Vandal Resistant	Yes
Frame Rate at Resolution	15
Day/Night Mode	Auto
Image Enhancement	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue
Video Compression	H.265, H.264 (3 streams)
Audio Streaming	Yes – input connector for external mic
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SNMP, P2P (QR code)
Intelligent Video	Video Analytics (Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection, Face Detection, Cross Counting)
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app
Power Over Ethernet	Yes
Ethernet	Ethernet (10/100 Base-T)
UPNP	Yes
In The Box	Free Software available from FAQ, Printed quick user guide, installation template, mounting screws and plugs
Warranty	3 Year Warranty