



NC691XB Security Camera

With smart tracking this 5MP image sensor also has long range IR 150 with a 33 times zoom lens. This camera is very impressive when patrolling large properties.

5
MEGA
PIXELS

4.3-142mm
LENS

Specifications

Camera Type	PTZ
Image Sensor	1/2.7" Progressive Scan CMOS
Maximum Video Resolution (Megapixels)	5MP (2592x1944)
Frames Per Second (FPS)	25
Lens	4.3mm - 142mm (H.FOV: 55 to 2.3°)
Lens Type	Motorised Pan, Tilt and Zoom
Maximum Night IR Distance (M)	150
Video Compression	H.265+, H.265, H.264+, H.264, MJPEG
ONVIF depends on firmware version	ONVIF (Profile S/G/T), HTTPAPI
Accessories	IV2488X
Outdoor Use	Yes
IP Rating	IP66
Vandal Resistant	Yes
Day/Night Mode	Auto
Image Enhancement	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction
Intelligent Video (IVS)	Face Recognition, Human & Vehicle Detection, Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map
Edge Recording microSD/SDHC Card	Micro SD/SDHC Card
Multiple Streams (encode format)	4 Streams
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, P2P (QR code)
Cloud option (camera only)	Dropbox
Audio Streaming	Yes - input connector for external mic
Ethernet	Ethernet (10/100 Base-T)
Power Over Ethernet	Yes
Power Supply	Power over Ethernet IEEE 802.3at, DC12V
Power Consumption	< 26W
Connectors	RJ-45, DC Power Input, Audio In, Audio Out, Alarm in and out.
Operating Environment	(-)30°C to 60°C (-22°F-149°F) Humidity: ≤90% RH
In The Box	Free Software available from FTP, Printed quick user guide, Installation template, Mounting screws and plugs
Product Dimensions (H x W x L) mm	206.4 x 206.4 x 351.8
Weight (Net) kg	3.7
Warranty	3 Year Warranty