

Delock External Enclosure for M.2 NVMe PCIe SSD with SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female

Description

This enclosure by Delock enables the installation of an **M.2 PCIe NVMe SSD** in 2280, 2260, 2242 and 2230 format, it can be connected via USB to the PC or laptop. The robust metal housing ensures an optimum temperature of the memory.



Specification

- Connectors:
 - external: 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
 - internal: 1 x 67 pin M.2 key M slot
- Chipset: Realtek RTL9210
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Data transfer rate up to 10 Gbps
- LED indicator for power and access
- Metal housing
- Dimensions (LxWxH): ca. 104 x 28 x 11 mm
- Hot Plug, Plug & Play

System requirements

- Linux Kernel 3.3 or above
- Mac OS 10.15.2 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ port

Package content

- External enclosure M.2
- Mounting material
- Cable USB-C™ male to USB-C™ male, length ca. 30 cm
- Cable USB-C™ male to USB Type-A male, length ca. 30 cm
- 1 x thermal pad
- User manual

Item no. 42634

EAN: 4043619426348

Country of origin: China

Package: • Retail Box



Images



| General | |
|---|--|
| Function: | NVM Express (NVMe) Hot Plug Plug & Play |
| Internal construction: | full PCB |
| Supported operating system: | Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 3.3 or above Mac OS 10.15.2 or above |
| Supported module: | M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe |
| Maximum height of the components on the module: | 1.5 mm application of double-sided assembled modules supported |
| Interface | |
| External: | 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female |
| Internal: | 1 x 67 pin M.2 key M slot |
| Technical characteristics | |
| Chipset: | Realtek RTL9210 |
| Data transfer rate: | up to 10 Gbps |
| Physical characteristics | |
| Housing material: | Aluminium |
| Cable length: | 30 cm |
| Length: | 104 mm |
| Width: | 28 mm |
| Height: | 11 mm |
| Colour: | silver |