

Delock 3.5" Mobile Rack for 1 x 2.5" SATA HDD / SSD

Description

This Delock Mobile Rack is designed for external or internal connection of a 2.5" SATA HDD. Insert the HDD directly into the frame and connect it either externally to a Power Over eSATA port with the help of an optional cable, or internally to SATA. The dimension of the frame complies to a standard 3.5" HDD. Thus you can install the frame into a 3.5" slot as well as into a 5.25" mobile rack.



Specification

- Connectors:
 - outside: 1 x SATA 22 pin plug
 - inside: 1 x SATA 22 pin receptacle (NSS connector)
- Suitable for 2.5" SATA HDD / SSD:
 - HDD height up to 12.5 mm
 - SATA HDD / SSD up to 6 Gb/s
 - supports 5 V HDD / SSD
- Data transfer rate up to 6 Gb/s
- Possible applications:
 1. internally in a 3.5" bay
 2. inside a 5.25" mobile rack
 3. externally over eSATAp (cable optional)
- Hot Swap
- With special SATA NSS connector inside to protect the SATA connector of the HDD from wear at each change
- Optional HDD fan (mounting holes on the bottom side of mobile rack)
- OS independent, no driver installation necessary

System requirements

- For external using:
 - PC or laptop with a free Power Over eSATA port (optional eSATAp cable item 84397 / 84396 / 84432)
- For internal using:
 - 1 SATA data cable
 - PC with a free SATA port
 - Power supply with a free SATA power connector

Package content

- Mobile Rack
- 1 x 2.5" hard drive protective film
- Screws
- User manual

Item no. 47224

EAN: 4043619472246

Country of origin: China

Package: Retail Box



Images



Anwendungsbeispiel

